



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006

SDS # : 37951

EQUIVIS XLT 15

Date of the previous version: 2015-03-24

Revision Date: 2018-01-17

Version 4.01

Section 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name	EQUIVIS XLT 15
Number	PEN
Substance/mixture	Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses	Hydraulic oil, Antiwear.
Sector of use	Lubricants.

1.3. Details of the supplier of the safety data sheet

Supplier	A - TOTAL BELGIUM Handelsstraat, 93, Rue du Commerce B-1040 BRUSSEL - BRUXELLES België - Belgique Tel : +32 (0)22 889 933 Fax : +32 (0)22 883 260
-----------------	---

B - TOTAL LUBRIFIANTS 562 Avenue du Parc de L'île 92029 Nanterre Cedex FRANCE Tél: +33 (0)1 41 35 40 00 Fax: +33 (0)1 41 35 84 71***
--

For further information, please contact:

Responsible/issuing person

Contact Point	A - HSE
---------------	----------------

E-mail Address	B - HSE***
----------------	-------------------

	A - rm.be-reach-belgium-msds@total.com
--	---

	B - rm.msds-lubs@total.com***
--	--------------------------------------

1.4. Emergency telephone number

Emergency telephone: +44 1235 239670

Teleserv S.O.S Total Belgium : +32 (0)78 15 51 51
 On duty staff in Ertvelde (Lub): +32 (0)475 66 07 77

Burns Centers:

Bruxelles - (NOH) - Brussel : +32 (0)2 264 48 48, Hopital Militaire Reine Astrid - Militair Hospitaal Koningin Astrid
 Antwerpen - Anvers : +32 (0)3 217 71 11, Algemeen centrum Ziekenhuis

Version EUBE



SDS # : 37951

EQUIVIS XLT 15

Revision Date: 2018-01-17

Version 4.01

Gent - Gand : +32 (0)9 240 34 90 Centre Universitaire UZ Gand-Universitair Ziekenhuis UZ Gent

Leuven - Louvain : +32 (0)16 34 87 50 U.Z. Leuven

Loverval : +32 (0)71 44 80 00, Hôpital Saint Joseph et Sainte Thérèse, section I.M.T.R

Luik - Liège : +32 (0)4 366 72 94, CHU Liège domaine Universitaire du Sart Tilman

Poison center:

c/o Hôpital Militaire Reine Astrid
 Militair Hospitaal Koningin Astrid
 1 Rue Bruyn - Bruynstraat 1
 B-1120 Bruxelles - Brussel
 +32 (0)70 245 245

Section 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

REGULATION (EC) No 1272/2008 ***

For the full text of the H-Statements mentioned in this Section, see Section 2.2. ***

Classification

The product is classified as dangerous in accordance with Regulation (EC) No. 1272/2008***

Aspiration toxicity - Category 1*** - (H304)***

Chronic aquatic toxicity - Category 3*** - (H412)***

2.2. Label elements

Labelled according to

REGULATION (EC) No 1272/2008***

Contains Hydrocarbons, C13-C16, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics, Distillates (petroleum), hydrotreated light paraffinic



Signal word

DANGER***

Hazard Statements ***

H304 - May be fatal if swallowed and enters airways

H412 - Harmful to aquatic life with long lasting effects***

Precautionary statements

P273 - Avoid release to the environment

P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor

P331 - Do NOT induce vomiting

P501 - Dispose of contents/ container to an approved waste disposal plant***

Version EUBE

SDS # : 37951

EQUIVIS XLT 15

Revision Date: 2018-01-17

Version 4.01

2.3. Other hazards

Physical-Chemical Properties

Contaminated surfaces will be extremely slippery.***

Environmental properties

The product may form an oil film on the water surface that may stop the oxygen exchange.***

Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixture***

Chemical nature

Mineral oil of petroleum origin.***

Hazardous components

Chemical Name	EC-No	REACH Registration Number	CAS-No	Weight %	Classification (Reg. 1272/2008)
Hydrocarbons, C13-C16, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics***	934-954-2***	01-2119826592-36	^	50-<60	Asp. Tox. 1 (H304)
Distillates (petroleum), hydrotreated light paraffinic***	265-158-7***	01-2119487077-29	64742-55-8	30-<40	Asp. Tox. 1 (H304)
Gas oils (petroleum), hydrodesulfurized***	265-182-8***	-	64742-79-6	2.5-<5	Acute Tox. 4 (H332) Skin Irrit. 2 (H315) Asp. Tox. 1 (H304) Aquatic Chronic 2 (H411)
Distillates (petroleum), hydrotreated middle***	265-148-2***	no data available	64742-46-7	1-<3	Asp. Tox. 1 (H304)

Additional information

Product containing mineral oil with less than 3% DMSO extract as measured by IP 346.***

For the full text of the H-Statements mentioned in this Section, see Section 16.

Section 4: FIRST AID MEASURES

4.1. Description of first aid measures

General advice

IN CASE OF SERIOUS OR PERSISTENT CONDITIONS, CALL A DOCTOR OR EMERGENCY MEDICAL CARE.***

Eye contact

Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Keep eye wide open while rinsing.***

Skin contact

Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Wash contaminated clothing before reuse. High pressure jets may cause skin damage. Take victim immediately to hospital.***

Inhalation

Remove casualty to fresh air and keep at rest in a position comfortable for breathing. If not breathing, give artificial respiration.***

Version EUBE

SDS # : 37951

EQUIVIS XLT 15

Revision Date: 2018-01-17

Version 4.01

Ingestion

Clean mouth with water. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a physician or poison control centre immediately.***

Protection of first-aiders

First aider needs to protect himself. See Section 8 for more detail. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.***

4.2. Most important symptoms and effects, both acute and delayed**Eye contact**

Not classified based on available data.***

Skin contact

Not classified based on available data. High pressure injection of the products under the skin may have very serious consequences even though no symptom or injury may be apparent.***

Inhalation

Not classified based on available data. Inhalation of vapours in high concentration may cause irritation of respiratory system.***

Ingestion

May be fatal if swallowed and enters airways. If swallowed accidentally, the product may enter the lungs due to its low viscosity and lead to the rapid development of very serious pulmonary lesions (medical survey during 48 hours).***

4.3. Indication of any immediate medical attention and special treatment needed**Notes to physician**

Treat symptomatically.***

Section 5: FIRE-FIGHTING MEASURES5.1. Extinguishing media**Suitable extinguishing media**

Carbon dioxide (CO₂). ABC powder. Foam. Water spray or fog.***

Unsuitable Extinguishing Media

Do not use a solid water stream as it may scatter and spread fire.

5.2. Special hazards arising from the substance or mixture**Special hazard**

Incomplete combustion and thermolysis may produce gases of varying toxicity such as carbon monoxide, carbon dioxide, various hydrocarbons, aldehydes and soot. These may be highly dangerous if inhaled in confined spaces or at high concentration. Combustion products include sulphur oxides (SO₂ and SO₃) and Hydrogen sulphide H₂S. Phosphorous oxides. Nitrogen oxides (NO_x). Mercaptans. Silicon dioxide.***

5.3. Precautions for fire-fighters**Special protective equipment for fire-fighters**

Wear self-contained breathing apparatus and protective suit.

Other information

Cool containers / tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

Version EUBE



SDS # : 37951

EQUIVIS XLT 15

Revision Date: 2018-01-17

Version 4.01

Section 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

General Information

Do not touch or walk through spilled material. Contaminated surfaces will be extremely slippery. Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition.***

6.2. Environmental precautions

General Information

Do not allow material to contaminate ground water system. Prevent entry into waterways, sewers, basements or confined areas. Local authorities should be advised if significant spillages cannot be contained.***

6.3. Methods and material for containment and cleaning up

Methods for containment

Dike to collect large liquid spills. If necessary dike the product with dry earth, sand or similar non-combustible materials.***

Methods for cleaning up

Dispose of contents/container in accordance with local regulation. In case of soil contamination, remove contaminated soil for remediation or disposal, in accordance with local regulations.***

6.4. Reference to other sections

Personal protective equipment

See Section 8 for more detail.

Waste treatment

See section 13.

Section 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Advice on safe handling

For personal protection see section 8. Use only in well-ventilated areas. Do not breathe vapours or spray mist. Avoid contact with skin, eyes and clothing.***

Prevention of fire and explosion

Take precautionary measures against static discharges.***

Hygiene measures

Ensure the application of strict rules of hygiene by the personnel exposed to the risk of contact with the product. When using, do not eat, drink or smoke. Wash hands before breaks and immediately after handling the product. Regular cleaning of equipment, work area and clothing is recommended. Do not use abrasives, solvents or fuels. Do not dry hands with rags that have been contaminated with product. Do not put product contaminated rags into workwear pockets.***

7.2. Conditions for safe storage, including any incompatibilities

Technical measures/Storage conditions

Keep away from food, drink and animal feedingstuffs. Keep in a bunded area. Keep container tightly closed. Preferably keep in the original container. Otherwise, reproduce all the statutory information from the labels onto the new container. Do not remove the hazard labels of the containers (even if they are empty). Design the installations in order to avoid



SDS # : 37951

EQUIVIS XLT 15

Revision Date: 2018-01-17

Version 4.01

accidental emissions of product (due to seal breakage, for example) onto hot casings or electrical contacts. Store at room temperature. Protect from moisture.***

Materials to avoid

Strong oxidising agents.***

7.3. Specific use(s)**Specific use(s)**

Please refer to Technical Data Sheet for further information.***

Section 8: EXPOSURE CONTROLS / PERSONAL PROTECTION8.1. Control parametres**Exposure limits**

Mineral oil mist:

USA: OSHA (PEL) TWA 5 mg/m³, NIOSH (REL) TWA 5 mg/m³, STEL 10 mg/m³, ACGIH (TLV) TWA 5 mg/m³ (highly refined)**Legend**

See section 16

Derived No Effect Level (DNEL)

DNEL Worker (Industrial/Professional)***

Chemical Name	Short term, systemic effects	Short term, local effects	Long term, systemic effects	Long term, local effects
Distillates (petroleum), hydrotreated light paraffinic*** 64742-55-8				5.4 mg/m ³ /8h (aerosol - inhalation)
Gas oils (petroleum), hydrodesulfurized*** 64742-79-6	5000 mg/m ³ /15 min [aerosol]		2.9 mg/kg/8h (dermal) 16 mg/m ³ /8h (aerosol - inhalation)	
Distillates (petroleum), hydrotreated middle*** 64742-46-7	5000 mg/m ³ /15 min (aerosol - inhalation)		2.9 mg/kg bw/8h (dermal) 16 mg/m ³ /8h (aerosol - inhalation)	

DNEL Consumer***

Chemical Name	Short term, systemic effects	Short term, local effects	Long term, systemic effects	Long term, local effects
Distillates (petroleum), hydrotreated light paraffinic*** 64742-55-8				1.2 mg/m ³ /24h (aerosol - inhalation)
Gas oils (petroleum), hydrodesulfurized*** 64742-79-6	3000 mg/m ³ /15 min (aerosol - inhalation)		1.3 mg/kg/8h (dermal) 4.8 mg/m ³ /8h (aerosol - inhalation)	
Distillates (petroleum), hydrotreated middle*** 64742-46-7	3000 mg/m ³ /15min (aerosol - inhalation)		1.3 mg/kg bw/8h (dermal) 4.8 mg/m ³ /8h (aerosol - inhalation)	

8.2. Exposure controls**Occupational Exposure Controls**

Version EUBE



SDS # : 37951

EQUIVIS XLT 15

Revision Date: 2018-01-17

Version 4.01

Engineering measures

Apply technical measures to comply with the occupational exposure limits. Ensure adequate ventilation, especially in confined areas. When working in confined spaces (tanks, containers, etc.), ensure that there is a supply of air suitable for breathing and wear the recommended equipment.***

Personal protective equipment**General Information**

Protective engineering solutions should be implemented and in use before personal protective equipment is considered. The personal protective equipment (PPE) recommendations apply to the product AS DELIVERED. In case of mixtures or formulations, it is suggested that you contact the relevant PPE suppliers.***

Respiratory protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Respirator with combination filter for vapour/particulate (EN 14387). Type A/P2. Warning ! filters have a limited use duration. The use of breathing apparatus must comply strictly with the manufacturer's instructions and the regulations governing their choices and uses.***

Eye protection

Safety glasses with side-shields. EN 166.***

Skin and body protection

Wear suitable protective clothing. Protective shoes or boots. Long sleeved clothing. Type 4/6.***

Hand protection

Hydrocarbon-proof gloves. Fluorinated rubber. Nitrile rubber. In case of prolonged contact with the product, it is recommended to wear gloves complying with EN 420 and EN 374 standards, protecting at least for 480 minutes and having a thickness of 0,38 mm at least. These values are indicative only. The level of protection is provided by the material of the glove, its technical characteristics, its resistance to the chemicals to be handled, the appropriateness of its use and its replacement frequency. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.***

Environmental exposure controls**General Information**

The product should not be allowed to enter drains, water courses or the soil.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES**9.1. Information on basic physical and chemical properties****Appearance**

Clear***

Colour

yellow***

Physical state @20°C

liquid***

Odour

characteristic***

Odour Threshold

No information available

Property**Values****Remarks****pH**

Not applicable***

Melting point/range

No information available***

Method

SDS # : 37951

EQUIVIS XLT 15

Revision Date: 2018-01-17

Version 4.01

Boiling point/boiling range	No information available***		
Flash point ***	>*** 110*** °C***		Cleveland Open Cup (COC)***
	>*** 230*** °F***		Cleveland Open Cup (COC)***
Evaporation rate		No information available***	
Flammability Limits in Air		***	
Upper ***	***	No information available***	***
Lower ***	***	No information available***	***
Vapour pressure		No information available***	
Vapour density		No information available***	
Relative density	0.845***	No information available***	
Density	845*** kg/m³***	@ 15 °C*** @ 15 °C*** Insoluble***	
Water solubility		No information available***	
Solubility in other solvents		No information available***	
logPow		No information available***	***
Autoignition temperature		No information available***	
Decomposition temperature		No information available***	
Viscosity, kinematic ***	*** 15*** mm²/s***	No information available @ 40 °C ***	ISO 3104 ***
Explosive properties	Not explosive***		
Oxidising properties	Not applicable***		
Possibility of hazardous reactions	None under normal processing***		

9.2. Other information

Freezing point	No information available
-----------------------	--------------------------

Section 10: STABILITY AND REACTIVITY

10.1. Reactivity

General Information	None under normal processing.***
----------------------------	----------------------------------

10.2. Chemical stability

Stability	Stable under recommended storage conditions.
------------------	--

10.3. Possibility of hazardous reactions

Hazardous reactions	No dangerous reaction known under conditions of normal use.***
----------------------------	--

10.4. Conditions to avoid

Conditions to avoid	Keep away from open flames, hot surfaces and sources of ignition. Keep away from heat and sparks.***
----------------------------	--

10.5. Incompatible materials

Materials to avoid	Strong oxidising agents.***
---------------------------	-----------------------------

SDS # : 37951

EQUIVIS XLT 15

Revision Date: 2018-01-17

Version 4.01

10.6. Hazardous Decomposition Products

Hazardous Decomposition Products Incomplete combustion and thermolysis may produce gases of varying toxicity such as carbon monoxide, carbon dioxide, various hydrocarbons, aldehydes and soot. Phosphorous oxides. Nitrogen oxides (NOx). Mercaptans. Combustion products include sulphur oxides (SO₂ and SO₃) and Hydrogen sulphide H₂S. Silicon dioxide.***

Section 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Acute toxicity Local effects Product Information

Skin contact

- Not classified based on available data. High pressure injection of the products under the skin may have very serious consequences even though no symptom or injury may be apparent.***

Eye contact

- Not classified based on available data.***

Inhalation

- Not classified based on available data. Inhalation of vapours in high concentration may cause irritation of respiratory system.***

Ingestion

- May be fatal if swallowed and enters airways. If swallowed accidentally, the product may enter the lungs due to its low viscosity and lead to the rapid development of very serious pulmonary lesions (medical survey during 48 hours).***

ATEmix (inhalation-dust/mist)

13.60*** mg/l***

ATEmix (inhalation-vapour)

1,256.20*** mg/l***

Acute toxicity - Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Hydrocarbons, C13-C16, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics***	LD50 > 5000 mg/kg bw (rat - OECD 401)	LD50 (24h) > 3160mg/kg bw (rabbit - OECD 402)	LC50 (4h) > 5266 mg/m ³ (aerosol) (rat - OECD 403)***
Distillates (petroleum), hydrotreated light paraffinic***	LD50 > 5000 mg/kg bw (rat - OECD 420)	LD50 > 5000 mg/kg bw (rabbit - OECD 402)	LC50 (4h) > 5 mg/l (aerosol) (rat - OECD 403)
Gas oils (petroleum), hydrodesulfurized***	LD50 > 5000 mg/kg bw (rat - OECD 401)	LD50 > 2000 mg/kg bw (rabbit - OECD 402)	LC50 (4h) 4.6 mg/l (aerosol) (rat - OECD 403)
Distillates (petroleum), hydrotreated middle***	> 5000 mg/kg bw (Rat - OECD TG 401)	> 2000 mg/kg bw 24h (Rabbit - OECD TG 402)	= 4.6 mg/l aerosol (4h- rat) OECD TG 403

Sensitisation

Sensitisation

Not classified based on available data.***

Specific effects

Carcinogenicity

Not classified based on available data.***

Mutagenicity

Germ cell mutagenicity

Not classified based on available data.***

Reproductive toxicity

Not classified based on available data.***

Version EUBE

SDS # : 37951

EQUIVIS XLT 15

Revision Date: 2018-01-17

Version 4.01

Repeated dose toxicity

Target Organ Effects (STOT)

Specific target organ systemic toxicity (single exposure) Not classified based on available data.***

Specific target organ toxicity - repeated exposure Not classified based on available data.***

Aspiration toxicity May be fatal if swallowed and enters airways. The fluid can enter the lungs and cause damage (chemical pneumonitis, potentially fatal).***

Other information

Other adverse effects Characteristic skin lesions (oil blisters) may develop following prolonged and repeated exposures (contact with contaminated clothing).***

Section 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Harmful to aquatic life with long lasting effects.***

Acute aquatic toxicity - Product Information***

No information available.***

Acute aquatic toxicity - Component Information

Chemical Name	Toxicity to algae	Toxicity to daphnia and other aquatic invertebrates.	Toxicity to fish	Toxicity to microorganisms
Hydrocarbons, C13-C16, n-alkanes, isoalkanes, cyclo, < 0.03% aromatics*** ^	ErL50 (72h) > 10000 mg/l (Skeletonema costatum - ISO 10253)	LL50 (48h) > 3193 mg/l (Acartia tonsa - ISO 14669)	LL50 (96h) > 1028 mg/l (Scophthalmus maximus - OECD 203)	
Distillates (petroleum), hydrotreated light paraffinic*** 64742-55-8	EL50 (48h) > 100 mg (Pseudokirchnerella subcapitata - OECD 201)	EL50 (48h) > 10000 mg/l (Daphnia magna - OECD 202)	LL50 (96h) > 100 mg/l (Oncorhynchus mykiss - OECD 203)	
Gas oils (petroleum), hydrodesulfurized*** 64742-79-6		EL50 (48h) 7.385 mg/l (Daphnia magna - QSAR Petrotox)	LL50 (96h) 21 mg/l (Oncorhynchus mykiss - OECD 203)	
Distillates (petroleum), hydrotreated middle*** 64742-46-7	ErL50 (72h) = 22 mg/l (OECD TG 201)	EL50 (48h) = 68 mg/l (OECD TG 202)	LL50 (96h) = 21 mg/l (OECD TG 203)	

Chronic aquatic toxicity - Product Information

No information available.***

Version EUBE

SDS # : 37951

EQUIVIS XLT 15

Revision Date: 2018-01-17

Version 4.01

Chronic aquatic toxicity - Component Information

Chemical Name	Toxicity to algae	Toxicity to daphnia and other aquatic invertebrates.	Toxicity to fish	Toxicity to microorganisms
Hydrocarbons, C13-C16, n-alkanes, isoalkanes, cyclo, < 0.03% aromatics*** ^		NOELR (21d) > 1000 mg/l (Daphnia magna - QSAR Petrotox)	NOELR (28d) > 1000 mg/l (Oncorhynchus mykiss - QSAR Petrotox)	
Distillates (petroleum), hydrotreated light paraffinic*** 64742-55-8		NOEL (21d) 10 mg/l (Daphnia magna - OECD 211)	NOEL (14/21d) > 1000 mg/l (Oncorhynchus mykiss - QSAR Petrotox)	
Gas oils (petroleum), hydrodesulfurized*** 64742-79-6		NOEL (21d) 0.163 mg/l (Daphnia magna - QSAR Petrotox)		
Distillates (petroleum), hydrotreated middle*** 64742-46-7		NOEL (21d) = 0.163 mg/l (QSAR modelled data)	NOEL (14d) = 0.069 mg/l (QSAR modelled data)	

Effects on terrestrial organisms

No information available.***

12.2. Persistence and Degradability

General Information

No information available.

12.3. Bioaccumulative potential

Product Information

No information available.***

logPow

Component Information

No information available.***

No information available.***

12.4. Mobility in soil

Soil

Given its physical and chemical characteristics, the product generally shows low soil mobility.***

Air

Loss by evaporation is limited.***

Water

The product is insoluble and floats on water.***

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment

No information available.***

12.6. Other adverse effects

General Information

No information available.***



SDS # : 37951

EQUIVIS XLT 15

Revision Date: 2018-01-17

Version 4.01

Section 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste from residues / unused products	Should not be released into the environment. Do not empty into drains. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations. Where possible recycling is preferred to disposal or incineration.***
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal.***
EWC Waste Disposal No	According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. Waste codes should be assigned by the user based on the application for which the product was used. The following Waste Codes are only suggestions: 13 01 10.***
Other information	Refer to section 8 for safety and protective measures for disposal personnel.***

Section 14: TRANSPORT INFORMATION

<u>ADR/RID</u>	not regulated
<u>IMDG/IMO</u>	not regulated
<u>ICAO/IATA</u>	not regulated
<u>ADN</u>	***
<u>UN/ID No</u>	ID9006***
<u>Proper shipping name</u>	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.***
<u>Hazard Class</u>	9***
<u>Hazard Labels</u>	none***
<u>Description</u>	ID9006, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S., 9 (Gas oils (petroleum), hydrodesulfurized)***
<u>Equipment Requirements</u>	PP***

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Further information

Version EUBE



SDS # : 37951

EQUIVIS XLT 15

Revision Date: 2018-01-17

Version 4.01

No information available***

15.2. Chemical Safety Assessment

Chemical Safety Assessment No information available***

15.3. National regulatory information

Belgium

- Avoid exceeding occupational exposure limits (see section 8).

Section 16: OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3

H304 - May be fatal if swallowed and enters airways

H315 - Causes skin irritation

H332 - Harmful if inhaled

H411 - Toxic to aquatic life with long lasting effects

H412 - Harmful to aquatic life with long lasting effects***

Abbreviations, acronyms

ACGIH = American Conference of Governmental Industrial Hygienists

bw = body weight

bw/day = body weight/day

EC x = Effect Concentration associated with x% response

GLP = Good Laboratory Practice

IARC = International Agency for Research of Cancer

LC50 = 50% Lethal concentration - Concentration of a chemical in air or a chemical in water which causes the death of 50% (one half) of a group of test animals

LD50 = 50% Lethal Dose - Chemical amount, given at once, which causes the death of 50% (one half) of a group of test animals

LL = Lethal Loading

NIOSH = National Institute of Occupational Safety and Health

NOAEL = No Observed Adverse Effect Level

NOEC = No Observed Effect Concentration

NOEL = No Observed Effect Level

OECD = Organization for Economic Co-operation and Development

OSHA = Occupational Safety and Health Administration

UVCB = Substance of unknown or Variable composition, Complex reaction products or Biological material

DNEL = Derived No Effect Level

PNEC = Predicted No Effect Concentration

dw = dry weight

fw = fresh water

mw = marine water

or = occasional release

Legend Section 8

TWA: Time Weight Average

STEL: Short Time Exposure Limit

Version EUBE



SDS # : 37951

EQUIVIS XLT 15

Revision Date: 2018-01-17

Version 4.01

+	Sensitiser	*	Skin designation
**	Hazard Designation	C:	Carcinogen
M:	Mutagen	R:	Toxic to reproduction

Revision Date: 2018-01-17

Revision Note *** Indicates updated section.

This safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006

This safety data sheet serves to complete but not to replace the technical product sheets. The information contained herein is given in good faith and is accurate to the best of knowledge at the date indicated above. It is understood by the user that any use of the product for purposes other than those for which it was designed entails potential risk. The information given herein in no way dispenses the user from knowing and applying all provisions regulating his activity. The user bears sole liability for the precautions required when using the product. The regulatory texts indicated herein are intended to aid the user to fulfil his obligations. This list is not to be considered complete and exhaustive. It is the user's responsibility to ensure that he is subject to no other obligations than those mentioned.

End of Safety Data Sheet

Version EUBE