

SAFETY DATA SHEET

1. Identification

Product identifier	Markers, GPX Classic (Xylene)	
Other means of identification	None.	
Recommended use	Marking.	
Recommended restrictions	None known.	
Manufacturer/Importer/Supplier/Distributor information		
Company name	Diagraph Marking & Coding	
Address	5307 Meadowland Parkway Marion IL 62959	
Telephone	1-800-521-3047	
E-mail	msds@diagraphmsp.com	
Contact person	Customer Service	
Emergency phone number	Emergency telephone	800-535-5053 (US only) +1-352-323-3500 international

2. Hazard(s) identification

Physical hazards	Flammable liquids	Category 3
Health hazards	Acute toxicity, dermal	Category 4
	Acute toxicity, inhalation	Category 4
	Skin corrosion/irritation	Category 2
	Serious eye damage/eye irritation	Category 2
	Carcinogenicity	Category 2
	Specific target organ toxicity, single exposure	Category 3 respiratory tract irritation
	Specific target organ toxicity, single exposure	Category 3 narcotic effects
	Specific target organ toxicity, repeated exposure	Category 2 (Central nervous system, Liver, Kidney)
Environmental hazards	Hazardous to the aquatic environment, acute hazard	Category 2
OSHA defined hazards	Not classified.	
Label elements		



Signal word Danger

Hazard statement Flammable liquid and vapor. May be fatal if swallowed and enters airways. Harmful in contact with skin. Causes skin irritation. Causes serious eye irritation. Harmful if inhaled. May cause respiratory irritation. May cause drowsiness or dizziness. Suspected of causing cancer. May cause damage to organs through prolonged or repeated exposure. Toxic to aquatic life.

Precautionary statement

Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe mist or vapor. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. Avoid release to the environment.

Response	If exposed or concerned: Get medical advice/attention. If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash before reuse. In case of fire: Use appropriate media to extinguish.
Storage	Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.
Hazard(s) not otherwise classified (HNOC)	None known.
Supplemental information	None.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
Xylene (mix)	1330-20-7	40-80
Titanium dioxide	13463-67-7	0-30
Ethylbenzene	100-41-4	5-20
1-Methoxy-2-propanol	107-98-2	0-20
Carbon black	1333-86-4	0-10
Kaolin, calcined	92704-41-1	0-10
2-Methoxy-1-methylethyl acetate	108-65-6	0-5
1-Propanol	71-23-8	0-2.9
Cumene	98-82-8	0.4 - 0.8
Toluene	108-88-3	<0.2

Composition comments All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or artificial respiration if needed. Call a POISON CENTER or doctor/physician if you feel unwell.
Skin contact	Take off immediately all contaminated clothing. Rinse skin with water/shower. Get medical advice/attention if you feel unwell. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Ingestion	Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.
Most important symptoms/effects, acute and delayed	Abdominal pain. Decrease in motor functions. Behavioral changes. Narcosis. Nausea, vomiting. Headache. May cause drowsiness and dizziness. Aspiration may cause pulmonary edema and pneumonitis. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. Skin irritation. May cause redness and pain. Edema. Jaundice. Prolonged exposure may cause chronic effects.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim warm. Keep victim under observation. Symptoms may be delayed.
General information	Take off all contaminated clothing immediately. IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO ₂).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	Flammable liquid and vapor.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	<p>Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools. Prevent product from entering drains.</p> <p>Large Spills: Stop the flow of material, if this is without risk. A vapor-suppressing foam may be used to reduce vapors. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.</p> <p>Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.</p>
Environmental precautions	<p>Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.</p> <p>Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.</p>

7. Handling and storage

Precautions for safe handling	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Do not breathe mist or vapor. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. When using, do not eat, drink or smoke. Should be handled in closed systems, if possible. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Wash contaminated clothing before reuse. Observe good industrial hygiene practices.
Conditions for safe storage, including any incompatibilities	Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
1-Propanol (CAS 71-23-8)	PEL	500 mg/m ³ 200 ppm	

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
Carbon black (CAS 1333-86-4)	PEL	3.5 mg/m ³	
Cumene (CAS 98-82-8)	PEL	245 mg/m ³	
Ethylbenzene (CAS 100-41-4)	PEL	50 ppm 435 mg/m ³	
Titanium dioxide (CAS 13463-67-7)	PEL	100 ppm 15 mg/m ³	Total dust.
Xylene (mix) (CAS 1330-20-7)	PEL	435 mg/m ³ 100 ppm	

US. OSHA Table Z-2 (29 CFR 1910.1000)

Components	Type	Value	Form
Toluene (CAS 108-88-3)	Ceiling TWA	300 ppm 200 ppm	

US. OSHA Table Z-3 (29 CFR 1910.1000)

Components	Type	Value	Form
Titanium dioxide (CAS 13463-67-7)	TWA	5 mg/m ³ 15 mg/m ³ 50 mppcf 15 mppcf	Respirable fraction. Total dust. Total dust. Respirable fraction.

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
1-Methoxy-2-propanol (CAS 107-98-2)	STEL TWA	100 ppm 50 ppm	
1-Propanol (CAS 71-23-8)	TWA	100 ppm	
Carbon black (CAS 1333-86-4)	TWA	3 mg/m ³	Inhalable fraction.
Cumene (CAS 98-82-8)	TWA	50 ppm	
Ethylbenzene (CAS 100-41-4)	TWA	20 ppm	
Titanium dioxide (CAS 13463-67-7)	TWA	10 mg/m ³	
Toluene (CAS 108-88-3)	TWA	20 ppm	
Xylene (mix) (CAS 1330-20-7)	STEL TWA	150 ppm 100 ppm	

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form
1-Methoxy-2-propanol (CAS 107-98-2)	STEL TWA	540 mg/m ³ 150 ppm 360 mg/m ³ 100 ppm	
1-Propanol (CAS 71-23-8)	STEL TWA	625 mg/m ³ 250 ppm 500 mg/m ³ 200 ppm	
Carbon black (CAS 1333-86-4)	TWA	3.5 mg/m ³	
Cumene (CAS 98-82-8)	TWA	245 mg/m ³ 50 ppm	

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
Ethylbenzene (CAS 100-41-4)	STEL	545 mg/m ³
		125 ppm
	TWA	435 mg/m ³
Toluene (CAS 108-88-3)		100 ppm
	STEL	560 mg/m ³
	TWA	150 ppm 375 mg/m ³ 100 ppm

Biological limit values**ACGIH Biological Exposure Indices**

Components	Value	Determinant	Specimen	Sampling Time
Ethylbenzene (CAS 100-41-4)	0.15 g/g	Sum of mandelic acid and phenylglyoxylic acid	Creatinine in urine	*
Toluene (CAS 108-88-3)	0.3 mg/g	o-Cresol, with hydrolysis	Creatinine in urine	*
	0.03 mg/l	Toluene	Urine	*
	0.02 mg/l	Toluene	Blood	*
Xylene (mix) (CAS 1330-20-7)	1.5 g/g	Methylhippuric acids	Creatinine in urine	*

* - For sampling details, please see the source document.

Exposure guidelines**US - California OELs: Skin designation**

1-Methoxy-2-propanol (CAS 107-98-2)	Can be absorbed through the skin.
1-Propanol (CAS 71-23-8)	Can be absorbed through the skin.
Cumene (CAS 98-82-8)	Can be absorbed through the skin.
Toluene (CAS 108-88-3)	Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

1-Propanol (CAS 71-23-8)	Skin designation applies.
Cumene (CAS 98-82-8)	Skin designation applies.
Toluene (CAS 108-88-3)	Skin designation applies.

US - Tennessee OELs: Skin designation

Cumene (CAS 98-82-8)	Can be absorbed through the skin.
----------------------	-----------------------------------

US. NIOSH: Pocket Guide to Chemical Hazards

1-Propanol (CAS 71-23-8)	Can be absorbed through the skin.
Cumene (CAS 98-82-8)	Can be absorbed through the skin.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Cumene (CAS 98-82-8)	Can be absorbed through the skin.
----------------------	-----------------------------------

Appropriate engineering controls

Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

Individual protection measures, such as personal protective equipment

Eye/face protection Chemical respirator with organic vapor cartridge and full facepiece. Wear safety glasses with side shields (or goggles) and a face shield.

Skin protection

Hand protection The following glove materials are recommended: Nitrile.
Full contact: Use gloves classified protection index 3 with breakthrough time of 5 minutes.
Minimum glove thickness 0.4 ± 0.05 mm.

Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Respiratory protection Chemical respirator with organic vapor cartridge and full facepiece.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties**Appearance**

Physical state	Liquid.
Form	Liquid.
Color	According to product specification.

Odor	Characteristic.
Odor threshold	Not available.
pH	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	248 °F (120 °C)
Flash point	75.2 °F (24.0 °C)
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable.

Upper/lower flammability or explosive limits

Flammability limit - lower (%)	1 % v/v
Flammability limit - upper (%)	7.8 % v/v
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.

Vapor pressure	9.5 hPa at 20°C.
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Fully miscible.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Explosive properties	Not explosive.
Oxidizing properties	Not oxidizing.

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong acids. Strong oxidizing agents. Halogens.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information**Information on likely routes of exposure**

Inhalation	Harmful if inhaled. May cause damage to organs through prolonged or repeated exposure by inhalation. May cause irritation to the respiratory system. May cause drowsiness and dizziness.
-------------------	--

Skin contact Harmful in contact with skin. Causes skin irritation.

Eye contact Causes serious eye irritation.

Ingestion Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.

Symptoms related to the physical, chemical and toxicological characteristics Abdominal pain. Behavioral changes. Decrease in motor functions. Narcosis. Nausea, vomiting. Jaundice. Aspiration may cause pulmonary edema and pneumonitis. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. May cause drowsiness and dizziness. Skin irritation. May cause redness and pain. Edema.

Information on toxicological effects

Acute toxicity Harmful if inhaled. Harmful in contact with skin. May be fatal if swallowed and enters airways.

Components	Species	Test Results
1-Methoxy-2-propanol (CAS 107-98-2)		
Acute		
Dermal		
LD50	Rabbit	13000 mg/kg
Inhalation		
LC50	Rat	>= 6 mg/l, 4 Hours
Oral		
LD50	Rat	> 5000 mg/kg
Carbon black (CAS 1333-86-4)		
Acute		
Dermal		
LD50	Rabbit	> 3000 mg/kg
Oral		
LD50	Rat	> 8000 mg/kg
Cumene (CAS 98-82-8)		
Acute		
Dermal		
LD50	Rabbit	> 3160 mg/kg, 24 Hours
Inhalation		
LC50	Rat	8000 ppm, 4 Hours
Oral		
LD50	Rat	2910 mg/kg
Ethylbenzene (CAS 100-41-4)		
Acute		
Dermal		
LD50	Rabbit	15400 mg/kg
Inhalation		
LC50	Rat	17.4 mg/l, 4 hours
Oral		
LD50	Rat	3500 - 4700 mg/kg
Toluene (CAS 108-88-3)		
Acute		
Dermal		
LD50	Rabbit	12200 mg/kg
Inhalation		
<i>Vapor</i>		
LC50	Rat	28.1 mg/l, 4 Hours

Components	Species	Test Results
Xylene (mix) (CAS 1330-20-7)		
Acute		
Oral		
LD50	Rat	3523 mg/kg
Skin corrosion/irritation	Causes skin irritation.	
Serious eye damage/eye irritation	Causes serious eye irritation.	
Respiratory or skin sensitization		
Respiratory sensitization	Not a respiratory sensitizer.	
Skin sensitization	This product is not expected to cause skin sensitization.	
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.	
Carcinogenicity	Suspected of causing cancer.	
IARC Monographs. Overall Evaluation of Carcinogenicity		
Carbon black (CAS 1333-86-4)	2B Possibly carcinogenic to humans.	
Cumene (CAS 98-82-8)	2B Possibly carcinogenic to humans.	
Ethylbenzene (CAS 100-41-4)	2B Possibly carcinogenic to humans.	
Titanium dioxide (CAS 13463-67-7)	2B Possibly carcinogenic to humans.	
Toluene (CAS 108-88-3)	3 Not classifiable as to carcinogenicity to humans.	
Xylene (mix) (CAS 1330-20-7)	3 Not classifiable as to carcinogenicity to humans.	
NTP Report on Carcinogens		
Cumene (CAS 98-82-8)	Reasonably Anticipated to be a Human Carcinogen.	
OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)		
Not regulated.		
Reproductive toxicity	This product is not expected to cause reproductive or developmental effects. The product contains a small amount of substance that is suspected of damaging fertility or the unborn child.	
Specific target organ toxicity - single exposure	May cause respiratory irritation. May cause drowsiness and dizziness.	
Specific target organ toxicity - repeated exposure	May cause damage to organs (Central nervous system, Liver, Kidney) through prolonged or repeated exposure.	
Aspiration hazard	May be fatal if swallowed and enters airways.	
Chronic effects	May cause damage to organs through prolonged or repeated exposure. Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.	
Further information	No data available.	

12. Ecological information

Components	Species	Test Results
Carbon black (CAS 1333-86-4)		
Aquatic		
<i>Acute</i>		
Fish	LC50	Leuciscus idus
		>= 1000 mg/l, 96 Hours
Cumene (CAS 98-82-8)		
Aquatic		
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)
		2.7 mg/l, 96 hours
Ethylbenzene (CAS 100-41-4)		
Aquatic		
<i>Acute</i>		
Crustacea	EC50	Water flea (Daphnia magna)
		1.81 - 2.38 mg/l, 48 hours
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)
		4.2 mg/l, 96 hours

Components	Species		Test Results
<i>Chronic</i>			
Crustacea	EC50	Ceriodaphnia dubia	3.6 mg/l, 7 days
Toluene (CAS 108-88-3)			
Aquatic			
<i>Acute</i>			
Crustacea	EC50	Daphnia magna	11.5 mg/l, 48 hours
Fish	LC50	Oncorhynchus kisutch	5.5 mg/l, 96 hours
<i>Chronic</i>			
Crustacea	NOEC	Ceriodaphnia dubia	0.74 mg/l, 7 days
Fish	NOEC	Oncorhynchus kisutch	1.4 mg/l, 40 days
Xylene (mix) (CAS 1330-20-7)			
Aquatic			
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	2.6 mg/l, 96 hours

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

Ethylbenzene (CAS 100-41-4)	3.15
Toluene (CAS 108-88-3)	2.73
Xylene (mix) (CAS 1330-20-7)	3.12 - 3.2

Mobility in soil No data available.

Other adverse effects The product contains volatile organic compounds which have a photochemical ozone creation potential.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

Waste from residues / unused products Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT

UN number	UN1210
UN proper shipping name	Printing ink, flammable
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Label(s)	3
Packing group	III
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Special provisions	B1, IB3, T2, TP1
Packaging exceptions	150
Packaging non bulk	173
Packaging bulk	242

IATA

UN number	UN1210
UN proper shipping name	Printing ink

Transport hazard class(es)

Class 3
Subsidiary risk -
Label(s) 3

Packing group III

Environmental hazards No

ERG Code 3L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

IMDG

UN number UN1210

UN proper shipping name PRINTING INK

Transport hazard class(es)

Class 3

Subsidiary risk -

Label(s) 3

Packing group III

Environmental hazards

Marine pollutant No

EmS F-E, S-D

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not established.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Cumene (CAS 98-82-8) Listed.

Ethylbenzene (CAS 100-41-4) Listed.

Toluene (CAS 108-88-3) Listed.

Xylene (mix) (CAS 1330-20-7) Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)**SARA 302 Extremely hazardous substance**

Not listed.

SARA 311/312 Hazardous chemical Yes

Classified hazard categories Flammable (gases, aerosols, liquids, or solids)
 Acute toxicity (any route of exposure)
 Skin corrosion or irritation
 Serious eye damage or eye irritation
 Carcinogenicity
 Specific target organ toxicity (single or repeated exposure)
 Aspiration hazard

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
Ethylbenzene	100-41-4	5-20
Xylene (mix)	1330-20-7	40-80

Other federal regulations**Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

Cumene (CAS 98-82-8)

Ethylbenzene (CAS 100-41-4)

Toluene (CAS 108-88-3)
Xylene (mix) (CAS 1330-20-7)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.

Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number

Toluene (CAS 108-88-3) 6594

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

Toluene (CAS 108-88-3) 35 %WV

DEA Exempt Chemical Mixtures Code Number

Toluene (CAS 108-88-3) 594

FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace

1-Propanol (CAS 71-23-8) Low priority

US state regulations

US. Massachusetts RTK - Substance List

1-Methoxy-2-propanol (CAS 107-98-2)
1-Propanol (CAS 71-23-8)
Carbon black (CAS 1333-86-4)
Cumene (CAS 98-82-8)
Ethylbenzene (CAS 100-41-4)
Titanium dioxide (CAS 13463-67-7)
Toluene (CAS 108-88-3)
Xylene (mix) (CAS 1330-20-7)

US. New Jersey Worker and Community Right-to-Know Act

1-Methoxy-2-propanol (CAS 107-98-2)
1-Propanol (CAS 71-23-8)
Carbon black (CAS 1333-86-4)
Cumene (CAS 98-82-8)
Ethylbenzene (CAS 100-41-4)
Titanium dioxide (CAS 13463-67-7)
Toluene (CAS 108-88-3)
Xylene (mix) (CAS 1330-20-7)

US. Pennsylvania Worker and Community Right-to-Know Law

1-Methoxy-2-propanol (CAS 107-98-2)
1-Propanol (CAS 71-23-8)
Carbon black (CAS 1333-86-4)
Cumene (CAS 98-82-8)
Ethylbenzene (CAS 100-41-4)
Titanium dioxide (CAS 13463-67-7)
Toluene (CAS 108-88-3)
Xylene (mix) (CAS 1330-20-7)

US. Rhode Island RTK

1-Methoxy-2-propanol (CAS 107-98-2)
1-Propanol (CAS 71-23-8)
Carbon black (CAS 1333-86-4)
Cumene (CAS 98-82-8)
Ethylbenzene (CAS 100-41-4)
Titanium dioxide (CAS 13463-67-7)
Toluene (CAS 108-88-3)
Xylene (mix) (CAS 1330-20-7)

California Proposition 65



WARNING: This product can expose you to chemicals including Benzene, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

California Proposition 65 - CRT: Listed date/Carcinogenic substance

1,4-Dioxane (CAS 123-91-1)	Listed: January 1, 1988
Benzene (CAS 71-43-2)	Listed: February 27, 1987
Carbon black (CAS 1333-86-4)	Listed: February 21, 2003
Cumene (CAS 98-82-8)	Listed: April 6, 2010

Ethylbenzene (CAS 100-41-4)	Listed: June 11, 2004
Naphthalene (CAS 91-20-3)	Listed: April 19, 2002
Titanium dioxide (CAS 13463-67-7)	Listed: September 2, 2011

California Proposition 65 - CRT: Listed date/Developmental toxin

Benzene (CAS 71-43-2)	Listed: December 26, 1997
Toluene (CAS 108-88-3)	Listed: January 1, 1991

California Proposition 65 - CRT: Listed date/Male reproductive toxin

Benzene (CAS 71-43-2)	Listed: December 26, 1997
-----------------------	---------------------------

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

1-Methoxy-2-propanol (CAS 107-98-2)
 Carbon black (CAS 1333-86-4)
 Cumene (CAS 98-82-8)
 Ethylbenzene (CAS 100-41-4)
 Titanium dioxide (CAS 13463-67-7)
 Toluene (CAS 108-88-3)
 Xylene (mix) (CAS 1330-20-7)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 19-April-2018
Revision date -
Version # 01
HMIS® ratings Health: 2*
 Flammability: 3
 Physical hazard: 0

NFPA ratings



Disclaimer

Diagraph Marking & Coding cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.