

# 12V MAX CXT™ LITHIUM-ION CORDLESS SELF-LEVELING CROSS-LINE GREEN BEAM LASER KIT (2.0AH)



**2.0Ah**  
BATTERY

**3**  
YEAR  
WARRANTY  
LITHIUM-ION  
TOOL & BATTERY


ALSO AVAILABLE AS A BARE TOOL: SK105GDZ

## PRODUCT HIGHLIGHTS



### VERSATILITY

Selectable horizontal/vertical cross lines required for level, align and plumb applications



### VISIBILITY

Green line visibility range up to 115' and detectable up to 262' with Makita Laser Detector



### COMPATIBILITY

12V max CXT™ battery delivers the convenience of a rechargeable tool battery



### DURABILITY

Integrated pendulum lock enables slope incline applications and provides added protection

## RELATED PRODUCTS

1. Wall/Ceiling Mount Bracket (LE00870137)
2. Green/Red Beam Laser Detector (LE00855702)
3. Compact Tripod (TKOLM1001F)
4. High Elevation Tripod (TKOLM5030F)
5. 18V LXT® Cordless Power Source (Power Source Only) (ADP05)



## NEW TOOL OVERVIEW SK105GDNAX



### FEATURES

- Bright 525 nm class II green laser for best-in-class visibility with +/- 1/8" at 33' for best-in-class accuracy
- Laser line fan angle spans past the 180° horizontal line and 160° vertical line positions for full reference line coverage
- Fast self-leveling line stability is achieved in up to 3 seconds for increased productivity
- Self-leveling is correctable up to 4° of slope allowing operation on uneven surfaces
- Dust and water resistance with IP 54 rating for increased durability
- Highly protected laser windows are recessed into the housing for increased durability
- Rubberized housing over-mold for increased protection
- Simplified one button user interface for ease of operation
- Low laser brightness mode conserve battery power for extended run-time performance

### SPECIFICATIONS

<b>Battery</b> .....	12V max CXT™ Lithium-Ion
<b>Line accuracy (at 33')</b> .....	+/- 1/8"
<b>Line beam direction</b> .....	2 line (horizontal, vertical)
<b>Working range (line)</b> .....	115'
<b>Working Range with Detector</b> .....	262'
<b>Operating time (hours)</b> .....	20
<b>Laser diode</b> .....	Class II, 510-530 nm
<b>Leveling range</b> .....	4°
<b>Debris resistance</b> .....	IP54 rating (dust & water resistance)
<b>Auto shut off</b> .....	No
<b>Net Weight</b> .....	1.9 lbs.
<b>UPC Code (SK105GDNAX)</b> .....	088381-878180
<b>UPC Code (SK105GDZ)</b> .....	088381-851909

### STANDARD EQUIPMENT

- 12V Max CXT™ Self-Leveling Cross-Line Green Beam Laser (SK105GDZ)
- 12V Max CXT™ Lithium-Ion 2.0Ah Battery (BL1021B)
- 18V LXT® / 12V Max CXT™ Lithium-Ion Rapid Optimum Charger (DC18RE)
- Magnetic L-Adapter (LE00870131)
- Green Laser Target Plate (LE00823195)
- Kit Bag (832173-9)