



Dry Moly Lube, 11 Wt Oz

No. 03084 | Item# 1003351 | Case# 1003350

Product Description Lowers friction, prevents galling and helps to reduce

torque and energy consumption. High anti-friction and anti-seizure properties. Fast drying film resists dirt and

dust build-up.

Applications Gaskets, transfer belts, conveyor belts, motors, plant

machinery and handling equipment, rubber moldings, high temperature, low load, or high rpm slides, rollers, wheels,

gears, chains & hoists

Unit Package Description 16 Ounce Aerosol

Brand CRC

Generic Description 1 Dry Film Lubricant

Net Fill 11 Wt Oz

UPC Code 078254030845

Unit Dimensions 7.75H x 2.63W x 2.63D in

Units Per Case 12

Case Dimensions 8.6H x 8.4W x 11.3D in

Cases Per Pallet 133
Case Weight 12 lbs

I 2 of 5 Code 30078254030846

Appearance Dark Gray Viscous Liquid
Base Type Molybdenum Disulfide

Flash point (F) -20° F Flash point (C) -29° C

Flammability Class - CPSC Extremely Flammable

Spec Gravity Concentrate 0.71
Plastic Safe No
Film Type Dry
Evaporation Rate Fast

Working Temp (F) 650°F (Continuous) / 750°F (Intermittent)
Working Temp (C) 343.3°C (Continuous) 398.9°C (Intermittent)

Last revised: 9/20/2019

Page 1 of 2







Propellant Hydrocarbon

Aerosol Flammability Level III

DOT Proper Shipping Name Aerosols, Flammable, Limited Quantity

VOC % (Consumer Product 61.8

def)

VOC g/L (Consumer 438.78

Product def)

VOC lbs/gal (Consumer

Prod def)

VOC Category Dry Film Lubricant

Removal (How To) Remove with a heavy duty degreaser.

3.66

Last revised: 9/20/2019

Page 2 of 2

