



Extreme Duty Silicone, 10 Wt Oz No. 03030 | Item# 1003285 | Case# 1003284

Product Description Silicone fluid with superior lubrication and temperature

viscosity characteristics. Use on all metallic and nonmetallic surfaces. Reduces friction and galling even on

metal-to-metal contact areas.

Applications Plant conveyors, guides and rails, mold release agents,

vending machines, electric motors and rollers and sliding

mechanisms

Unit Package Description 16 Ounce Aerosol

Brand CRC

Generic Description 1 Premium Grade Silicone Lubricant

Net Fill 10 Wt Oz

UPC Code 078254030302

Unit Dimensions 7.75H x 2.63W x 2.63D in

Units Per Case 12

Case Dimensions 8.1H x 8.3W x 11.1D in

Cases Per Pallet 133
Case Weight 11 lbs

I 2 of 5 Code 30078254030303

Appearance Clear Colorless Liquid

Base Type Silicone Flash point (F) <0°F Flash point (C) <-18°C

Flammability Class - CPSC Extremely Flammable

Spec Gravity Concentrate 0.6699

Plastic Safe Safe on Most Plastics (Test small area)

Film Type Dry Film

Film Thickness Not Determined

Evaporation Rate Fast

Dielectric Strength Not Determined
Working Temp (F) -100 to 450°F

Last revised: 9/5/2019

Page 1 of 2







Working Temp (C) 204.4°C Propellant HFC-152a

NSF Category Code H2

NSF Number 116808

Aerosol Flammability Level Ш

DOT Proper Shipping Name Aerosols, Flammable, Limited Quantity 60

VOC % (Consumer Product

def)

VOC g/L (Consumer 400.2

Product def)

VOC lbs/gal (Consumer

Prod def)

VOC Category Silicone Based Multi-Purpose Lubricant

3.34

Removal (How To) Mineral Spirits

Last revised: 9/5/2019

Page 2 of 2

