



Seal Coat® Red Urethane Coating, 11 Wt Oz

No. 18410 | Item# 1005236 | Case# 1005235

Product Description Polyurethane coating that insulates electrical equipment

and seals out water and moisture. The red formula allows

for visualization of equipment.

Applications On motor windings, terminals, bus bars, commutator

ends, stator coils, and PC boards

Unit Package Description 16 Ounce Aerosol

Brand CRC

Generic Description 1 Urethane Coating

Net Fill 11 Wt Oz

UPC Code 078254184104

Unit Dimensions 7.75H x 2.63W x 2.63D in

Units Per Case 12

Case Dimensions 8.6H x 8.4W x 11.3D in

Cases Per Pallet 133
Case Weight 11 lbs

I 2 of 5 Code 30078254184105 Appearance Red Viscous Liquid

Flash point (F) -4°F Flash point (C) -20°C

Flammability Class - CPSC Extremely Flammable

Spec Gravity Concentrate 0.731
Plastic Safe Yes

Evaporation Rate Moderate
Dry Time - Fully Dry 72 Hours

Dry Time - Tack Free 15 to 30 Minutes

Coverage 20 to 25 Sq Ft

Dielectric Strength 2,000 Volts/Mil

Working Temp (F) -90 to 250°F

Working Temp (C) -67.8 to 121.1°C

Last revised: 1/8/2020

Page 1 of 2







Propellant Hydrocarbon

Aerosol Flammability Level III

DOT Proper Shipping Name Aerosols, Flammable, Limited Quantity

VOC % (Consumer Product 57.1

def)

VOC g/L (Consumer 417.4

Product def)

VOC lbs/gal (Consumer 3.5

Prod def)

VOC Category Aerosol Coating: Electrical Coating

MIR Limit (EPA) None
MIR Limit (CA) 2.0

MIR Value 1.37

Removal (How To) Remove: WET paint with mineral spirits or terpentine, DRY

paint with lacquer thinner/stripper.

Last revised: 1/8/2020

Page 2 of 2

