

SAFETY DATA SHEET

1. Identification

Product identifier	3-36® Multi-Purpose Lubricant & Corrosior	n Inhibitor - 55 gal
Other means of identification		
Product Code	No. 03011 (Item# 1003262)	
Recommended use	Multi-purpose lubricant	
Recommended restrictions	None known.	
Manufacturer/Importer/Supplier/	Distributor information	
Manufactured or sold by:		
Company name	CRC Industries, Inc.	
Address	885 Louis Dr.	
	Warminster, PA 18974 US	
Telephone		
General Information	215-674-4300	
Technical Assistance	800-521-3168	
Customer Service	800-272-4620	
24-Hour Emergency	800-424-9300 (US)	
(CHEMTREC) Website	www.crcindustries.com	
	www.crcindustnes.com	
2. Hazard(s) identification		
Physical hazards	Flammable liquids	Category 4
Health hazards	Sensitization, skin	Category 1
	Aspiration hazard	Category 1
Environmental hazards	Not classified.	
OSHA defined hazards	Not classified.	
Label elements		
	\wedge	
Signal word	Danger	
Hazard statement	Combustible liquid. May be fatal if swallowed a reaction.	and enters airways. May cause an allergic skin
Precautionary statement		
Prevention	doors and windows or use other means to ensist drying. If you experience any symptoms listed	o smoking. Use with adequate ventilation. Open sure a fresh air supply during use and while product ed on this label, increase ventilation or leave the ted work clothing must not be allowed out of the tion/face protection
Response	If swallowed: Immediately call a poison center with plenty of water. If skin irritation or rash oc	/doctor. Do NOT induce vomiting. If on skin: Wash
Storage	Store in a well-ventilated place. Keep cool. Sto	pre locked up.
Disposal	Dispose of contents/container in accordance v	vith local/regional/national/international regulations.
Hazard(s) not otherwise classified (HNOC)	None known.	
Supplemental information	None.	

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
distillates (petroleum), hydrotreated light		64742-47-8	60 - 70
distillates (petroleum), hydrotreated heavy paraffinic		64742-54-7	5 - 10
paraffin oils (petroleum), catalytic dewaxed heavy		64742-70-7	5 - 10
paraffin oils (petroleum), catalytic dewaxed light		64742-71-8	5 - 10
butyl stearate		123-95-5	1 - 5
dipropylene glycol methyl ether acetate		88917-22-0	1 - 5
petrolatum		8009-03-8	1 - 5

Specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures	
Inhalation	Move to fresh air. Call a physician if symptoms develop or persist.
Skin contact	Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions.
Eye contact	Rinse with water. Get medical attention if irritation develops and persists.
Ingestion	Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.
Most important symptoms/effects, acute and delayed	Aspiration may cause pulmonary edema and pneumonitis. Headache. Nausea, vomiting. Diarrhea. Direct contact with eyes may cause temporary irritation. May cause an allergic skin reaction. Dermatitis. Rash.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media Unsuitable extinguishing media	Water fog. Alcohol resistant foam. Dry chemical powder. Dry chemicals. Carbon dioxide (CO2). Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	The product is combustible, and heating may generate vapors which may form explosive vapor/air mixtures. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire-fighting equipment/instructions	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk. Cool containers exposed to heat with water spray and remove container, if no risk is involved. Use standard firefighting procedures and consider the hazards of other involved materials.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	Combustible liquid. Will burn if involved in a fire.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapors. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up	Use water spray to reduce vapors or divert vapor cloud drift. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material.	
	Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.	
	Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.	
	Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.	
Environmental precautions	Avoid discharge into drains, water courses or onto the ground.	
7. Handling and storage		
Precautions for safe handling	Keep away from open flames, hot surfaces and sources of ignition. When using do not smoke. Avoid breathing mist/vapors. Avoid contact with eyes, skin, and clothing. Avoid prolonged or repeated contact with skin. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices. For product usage instructions, see the product label.	
Conditions for safe storage, including any incompatibilities	Keep away from heat and sources of ignition. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).	

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

U.S OSHA Components	Туре	Value	
distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)	TWA	5 mg/m3	
US. OSHA Table Z-1 Limits for Air Cor Components		Value	Form
•	Туре		-
distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)	PEL	5 mg/m3	Mist.
paraffin oils (petroleum), catalytic dewaxed heavy (CAS 64742-70-7)	PEL	5 mg/m3	Mist.
paraffin oils (petroleum), catalytic dewaxed light (CAS 64742-71-8)	PEL	5 mg/m3	Mist.
petrolatum (CAS 8009-03-8)	PEL	5 mg/m3	Mist.
ACGIH			
Components	Туре	Value	Form
distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)	TWA	5 mg/m3	Inhalable fraction
US. ACGIH Threshold Limit Values			
Components	Туре	Value	Form
butyl stearate (CAS 123-95-5)	TWA	3 mg/m3	Respirable fraction.
		10 mg/m3	Inhalable fraction.
distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)	TWA	5 mg/m3	Inhalable fraction.

US. ACGIH Threshold Limit Components	Values Type	Value	Form
paraffin oils (petroleum), catalytic dewaxed heavy (CAS 64742-70-7)	TWA	5 mg/m3	Inhalable fraction.
paraffin oils (petroleum), catalytic dewaxed light (CAS 64742-71-8)	TWA	5 mg/m3	Inhalable fraction.
petrolatum (CAS 8009-03-8)	TWA	5 mg/m3	Inhalable fraction.
U.S NIOSH Components	Туре	Value	Form
distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)	STEL	10 mg/m3	Mist
para	TWA	5 mg/m3	Mist
US. NIOSH: Pocket Guide to	Chemical Hazards		
Components	Туре	Value	Form
distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
distillates (petroleum), hydrotreated light (CAS 64742-47-8)	TWA	100 mg/m3	
paraffin oils (petroleum), catalytic dewaxed heavy (CAS 64742-70-7)	STEL	10 mg/m3	Mist.
· · ·	TWA	5 mg/m3	Mist.
paraffin oils (petroleum), catalytic dewaxed light (CAS 64742-71-8)	STEL	10 mg/m3	Mist.
· · ·	TWA	5 mg/m3	Mist.
petrolatum (CAS 8009-03-8)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
logical limit values	No biological exposure limits noted for	the ingredient(s).	
propriate engineering htrols	Good general ventilation should be us applicable, use process enclosures, lo maintain airborne levels below recom established, maintain airborne levels t	ocal exhaust ventilation, or othe mended exposure limits. If exp	er engineering controls to
ividual protection measures, Eye/face protection	such as personal protective equipme Wear safety glasses with side shields		
Skin protection Hand protection	Wear protective gloves such as: Neoprene. Nitrile.		
Other	Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.		
Respiratory protection	If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to determine actual employee exposure levels.		
Thermal hazards	Wear appropriate thermal protective c	lothing, when necessary.	
neral hygiene isiderations	When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should no be allowed out of the workplace.		

9. Physical and chemical properties

9. Physical and chemical	bioperties
Appearance	
Physical state	Liquid.
Form	Liquid.
Color	Blue green
Odor	Pleasant.
Odor threshold	Not available.
рН	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	380 °F (193.3 °C) estimated
Flash point	192 °F (88.9 °C) Setaflash
Evaporation rate	Slow.
Flammability (solid, gas)	Not available.
Upper/lower flammability or exp	osive limits
Flammability limit - lower (%)	0.5 % estimated
Flammability limit - upper (%)	5.5 % estimated
Vapor pressure	0.2 hPa estimated
Vapor density	> 1 (air = 1)
Relative density	0.83
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	410 °F (210 °C) estimated
Decomposition temperature	Not available.
Viscosity	Not available.
Percent volatile	78.5 % estimated

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	Carbon oxides. Sulfur oxides. Hydrogen sulfide. Mercaptans. Sulfides.

11. Toxicological information

Information on likely routes of exposure

Inhalation	Prolonged inhalation may be harmful.
Skin contact	May cause an allergic skin reaction.
Eye contact	Based on available data, the classification criteria are not met.
Ingestion	Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.
Symptoms related to the physical, chemical and toxicological characteristics	Aspiration may cause pulmonary edema and pneumonitis. Headache. Nausea, vomiting. Diarrhea. May cause an allergic skin reaction. Dermatitis. Rash.

Information on toxicological effects

Acute toxicity	May be fatal if swallowed ar	d enters airways.	
Components	Species	Test Results	
distillates (petroleum), hydrotreate	ed light (CAS 64742-47-8)		
<u>Acute</u>			
Dermal			
LD50	Rat	> 2000 mg/kg	
Inhalation	- /		
LC50	Rat	> 5 mg/l, 4 hours	
Oral		5000 # 0.51	
LD50	Rat	> 5000 mg/kg, 2.5 hours	
paraffin oils (petroleum), catalytic	dewaxed heavy (CAS 64742-7	0-7)	
<u>Acute</u>			
Dermal LD50	Rabbit	> 2000 mg/kg	
	Παρριτ	2000 mg/kg	
Oral LD50	Rat	> 5000 mg/kg	
paraffin oils (petroleum), catalytic <u>Acute</u>	uewaxeu ligili (UAS 04/42-71)	-0 <i>j</i>	
Dermal			
LD50	Rabbit	> 2000 mg/kg	
Oral			
LD50	Rat	> 5000 mg/kg	
Skin corrosion/irritation	Prolonged skin contact may		
Serious eye damage/eye	Direct contact with eyes ma		
irritation	Diroct contact min cyco ma		
Respiratory or skin sensitizatio	n		
Respiratory sensitization	Not a respiratory sensitizer.		
Skin sensitization	May cause an allergic skin r	eaction.	
Germ cell mutagenicity	No data available to indicate mutagenic or genotoxic.	product or any components present at greater than 0.1% are	
Carcinogenicity	Not classifiable as to carcine	ogenicity to humans.	
IARC Monographs. Overall	Evaluation of Carcinogenicit	У	
(CAS 64742-54-7)	ydrotreated heavy paraffinic	3 Not classifiable as to carcinogenicity to humans.	
paraffin oils (petroleum), (CAS 64742-71-8)	catalytic dewaxed light	3 Not classifiable as to carcinogenicity to humans.	
	ed Substances (29 CFR 1910	1001-1053)	
Not listed.			
	ogram (NTP) Report on Carc	inogens	
Not listed.			
Reproductive toxicity		to cause reproductive or developmental effects.	
Specific target organ toxicity - single exposure	Not classified.		
Specific target organ toxicity - repeated exposure	Not classified.		
Aspiration hazard	May be fatal if swallowed and enters airways.		
Chronic effects	Prolonged inhalation may be	harmful	

12. Ecological information

Ecotoxicity

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components		Species	Test Results	
distillates (petroleum), hydro	treated heavy	v paraffinic (CAS 64742-54-7)		
Aquatic				
Acute				
Crustacea	EC50	Water flea (Daphnia magna)	> 10000 mg/l, 48 hours	
Fish	LC50	Fathead minnow (Pimephales promelas)	> 100 mg/l, 96 hours	
distillates (petroleum), hydro	treated light (CAS 64742-47-8)		
Aquatic				
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	2.9 mg/l, 96 hours	
paraffin oils (petroleum), cata	alytic dewaxe	d light (CAS 64742-71-8)		
Aquatic				
Acute				
Crustacea	EC50	Daphnia	> 100 mg/l, 48 hours	
sistence and degradability	No data is	No data is available on the degradability of any ingredients in the mixture.		
accumulative potential				
bility in soil	No data a	No data available.		
er adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.			
. Disposal consideration	ons			
posal instructions	This product is not a RCRA hazardous waste (See 40 CFR Part 261.20 – 261.33), Empty			

Disposal instructions	This product is not a RCRA hazardous waste (See 40 CFR Part 261.20 – 261.33). Empty containers may be recycled. Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose in accordance with all applicable regulations.
Hazardous waste code	Not regulated.
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

CERCLA Hazardous Substances: Reportable quantity

Not listed.

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List Not regulated. Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130) Not regulated. Safe Drinking Water Act Not regulated. (SDWA) Food and Drug Not regulated. Administration (FDA) Superfund Amendments and Reauthorization Act of 1986 (SARA) **Classified hazard** Flammable (gases, aerosols, liquids, or solids) Respiratory or skin sensitization categories Aspiration hazard SARA 302 Extremely hazardous substance Not listed.

SARA 311/312 Hazardous Yes chemical

SARA 313 (TRI reporting)

Not regulated.

US state regulations

US. New Jersey Worker and Community Right-to-Know Act Not listed.

US. Massachusetts RTK - Substance List

distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7) paraffin oils (petroleum), catalytic dewaxed heavy (CAS 64742-70-7) paraffin oils (petroleum), catalytic dewaxed light (CAS 64742-71-8) petrolatum (CAS 8009-03-8)

US. Pennsylvania Worker and Community Right-to-Know Law

distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7) distillates (petroleum), hydrotreated light (CAS 64742-47-8) paraffin oils (petroleum), catalytic dewaxed heavy (CAS 64742-70-7) paraffin oils (petroleum), catalytic dewaxed light (CAS 64742-71-8) petrolatum (CAS 8009-03-8)

US. Rhode Island RTK

distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7) distillates (petroleum), hydrotreated light (CAS 64742-47-8) paraffin oils (petroleum), catalytic dewaxed heavy (CAS 64742-70-7) paraffin oils (petroleum), catalytic dewaxed light (CAS 64742-71-8) petrolatum (CAS 8009-03-8)

California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 2016 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins. For more information go to www.P65Warnings.ca.gov.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7) distillates (petroleum), hydrotreated light (CAS 64742-47-8) paraffin oils (petroleum), catalytic dewaxed heavy (CAS 64742-70-7) paraffin oils (petroleum), catalytic dewaxed light (CAS 64742-71-8) petrolatum (CAS 8009-03-8)

Volatile organic compounds (VOC) regulations

EPA

VOC content (40 CFR100 %51.100(s))Consumer productsConsumer productsNot regulated(40 CFR 59, Subpt. C)Vot regulated

State

State		
Consumer products	This product is regulated as a Multi-Purpose Lubricant. This product is states.	s compliant for use in all 50
VOC content (CA)	0 %	
VOC content (OTC)	0 %	
International Inventories		
Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes
	and the second	·····

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	03-28-2020
Prepared by	Allison Yoon
Version #	01
Further information	CRC # 510F/1002511
Disclaimer	The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC's knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety professional, or CRC Industries, Inc
Revision information	This document has undergone significant changes and should be reviewed in its entirety.