

## SAFETY DATA SHEET

## 1. Identification

Product identifier Gasoline 1-Tank Power Renew® - 15 fl oz

Other means of identification

Product Code No. 05815 (Item# 1003859)

Product registration

number

048320130

Registration number EPA: 048320130
Recommended use Gasoline fuel additive

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufactured or sold by:

Company name CRC Industries, Inc.

Address 885 Louis Dr.

Warminster, PA 18974 US

**Telephone** 

 General Information
 215-674-4300

 Technical Assistance
 800-521-3168

 Customer Service
 800-272-4620

 24-Hour Emergency
 800-424-9300 (US)

(CHEMTREC)

Website www.crcindustries.com

## 2. Hazard(s) identification

Physical hazardsFlammable liquidsCategory 4Health hazardsAcute toxicity, oralCategory 4Skin corrosion/irritationCategory 1BSerious eye damage/eye irritationCategory 1Sensitization, skinCategory 1Germ cell mutagenicityCategory 2

Carcinogenicity

Category 2

Aspiration hazard

Category 1

Hazardous to the aquatic environment, acute

Category 2

Category 2

Environmental hazards Hazardous to the aquatic environment, acute

hazard

Hazardous to the aquatic environment, Category 2

long-term hazard

OSHA defined hazards Not classified.

Label elements



Signal word Danger

**Hazard statement** Combustible liquid. Harmful if swallowed. May be fatal if swallowed and enters airways. Causes

severe skin burns and eye damage. May cause an allergic skin reaction. Suspected of causing

genetic defects. Suspected of causing cancer.

#### **Precautionary statement**

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read

and understood. Keep away from flames and hot surfaces-No smoking. Do not breathe vapor. Use with adequate ventilation. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves/protective clothing/eye protection/face protection.

Response If swallowed: Immediately call a poison center/doctor. Rinse mouth. Do NOT induce vomiting. If

on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse. If inhaled: Remove person to fresh air and keep comfortable for breathing. Immediately call a poison center/doctor. If in eyes: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. If exposed or concerned: Get medical advice/attention. In case of fire: Do not use

water jet as an extinguisher, as this will spread the fire.

Store in a well-ventilated place. Keep cool. Store locked up. **Storage** 

**Disposal** Dispose of contents/container in accordance with local/regional/national regulations.

Hazard(s) not otherwise classified (HNOC)

None known.

Supplemental information None.

## 3. Composition/information on ingredients

#### **Mixtures**

Chemical name	Common name and synonyms	CAS number	%
distillates (petroleum), hydrotreated light	1	64742-47-8	35 - 45
distillates (petroleum), hydrodesulfurized middle	Diesel Fuel No. 2	64742-80-9	20 - 30
polyether amine		Proprietary	20 - 30
alkyl aminoester		Proprietary	< 3

Specific chemical identity and/or percentage of composition has been withheld as a trade secret.

#### 4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist. If inhalation of a large amount

does occur, call a physician immediately.

Skin contact Remove contaminated clothing immediately and wash skin with soap and water. Call a physician

or poison control center immediately. Chemical burns must be treated by a physician. Wash

contaminated clothing before reuse.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Call a physician or poison control center immediately.

Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If

vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Most important symptoms/effects, acute and

delayed

Ingestion

Aspiration may cause pulmonary edema and pneumonitis. Headache. Dizziness. Nausea, vomiting. Diarrhea. Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Chemical burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area, Call an ambulance. Continue flushing during transport to hospital. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

**General information** IF exposed or concerned: Get medical advice/attention. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

## 5. Fire-fighting measures

Suitable extinguishing media Unsuitable extinguishing media

Water fog. Alcohol resistant foam. Dry chemical powder. Dry chemicals. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

The product is combustible, and heating may generate vapors which may form explosive vapor/air mixtures. During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Fire-fighting equipment/instructions

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk. Cool containers exposed to heat with water spray and remove container, if no risk is involved. Use standard firefighting procedures and consider the hazards of other involved

Specific methods
General fire hazards

Use standard firefighting procedures and consider the hazards of other involved materials.

Combustible liquid.

## 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not breathe vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Use water spray to reduce vapors or divert vapor cloud drift. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. This product is miscible in water. Prevent product from entering drains.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.

**Environmental precautions** 

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

## 7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from open flames, hot surfaces and sources of ignition. Do not get in eyes, on skin, or on clothing. Do not taste or swallow. Avoid prolonged or repeated contact with skin. Avoid prolonged exposure. When using, do not eat, drink or smoke. Should be handled in closed systems, if possible. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices. For product usage instructions, see the product label.

Conditions for safe storage, including any incompatibilities

Keep away from heat and sources of ignition. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

## 8. Exposure controls/personal protection

## Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

# US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) Components Type

**PEL** 

distillates (petroleum), hydrodesulfurized middle (CAS 64742-80-9)

(CAS 64742-80-9)

100 ppm

400 mg/m3

Value

## US. ACGIH Threshold Limit Values

ComponentsTypeValueFormdistillates (petroleum),<br/>hydrodesulfurized middleTWA5 mg/m3Inhalable fraction.

Material name: Gasoline 1-Tank Power Renew® - 15 fl oz

No. 05815 (Item# 1003859) Version #: 02 Revision date: 03-11-2020 Issue date: 08-13-2019 3 / 9

US. NIOSH: Pocket Guide to Chemical Hazards

distillates (petroleum), TWA 400 mg/m3 hydrodesulfurized middle

Type

(CAS 64742-80-9)

Components

100 ppm

Value

distillates (petroleum), hydrotreated light (CAS **TWA** 100 mg/m3

64742-47-8)

**Biological limit values** 

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station. Eye wash fountain and emergency showers are recommended.

Individual protection measures, such as personal protective equipment

Wear safety glasses with side shields (or goggles). Eye/face protection

Skin protection

Wear protective gloves such as: Nitrile. Neoprene. Polyvinyl chloride (PVC). **Hand protection** 

Other Wear appropriate chemical resistant clothing.

If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a Respiratory protection

NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to

determine actual employee exposure levels.

Wear appropriate thermal protective clothing, when necessary. Thermal hazards

General hygiene considerations

Observe any medical surveillance requirements. When using do not smoke.

## 9. Physical and chemical properties

**Appearance** 

**Physical state** Liquid. **Form** Liquid. Color Yellow. Petroleum. Odor **Odor threshold** Not available. Not available. Not available. Melting point/freezing point

Initial boiling point and boiling

range

120.2 °F (49 °C) estimated

Flash point 161.6 °F (72 °C) Setaflash

**Evaporation rate** Slow.

Not available. Flammability (solid, gas) Upper/lower flammability or explosive limits

Flammability limit - lower

0.5 % estimated

(%)

Flammability limit - upper

7.5 % estimated

(%)

0.3 hPa estimated Vapor pressure > 1 (air = 1)Vapor density

0.85 Relative density

Solubility(ies)

Solubility (water) Negligible. **Partition coefficient** Not available.

(n-octanol/water)

Auto-ignition temperature 410 °F (210 °C) estimated

Decomposition temperatureNot available.ViscosityNot available.Percent volatile69.5 % estimated

## 10. Stability and reactivity

**Reactivity** The product is stable and non-reactive under normal conditions of use, storage and transport.

**Chemical stability** Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Avoid

temperatures exceeding the flash point. Contact with incompatible materials.

Incompatible materials Strong oxidizing agents.

**Hazardous decomposition** 

products

Carbon oxides. Nitrogen oxides (NOx). Aldehydes. Hydrocarbon fumes and smoke.

## 11. Toxicological information

#### Information on likely routes of exposure

**Inhalation** May cause irritation to the respiratory system. Prolonged inhalation may be harmful.

**Skin contact** Causes severe skin burns. May cause an allergic skin reaction.

**Eye contact** Causes serious eye damage.

Ingestion Causes digestive tract burns. Harmful if swallowed. Droplets of the product aspirated into the

lungs through ingestion or vomiting may cause a serious chemical pneumonia.

Symptoms related to the physical, chemical and toxicological characteristics

Aspiration may cause pulmonary edema and pneumonitis. Headache. Dizziness. Nausea, vomiting. Diarrhea. Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye

damage including blindness could result.

#### Information on toxicological effects

**Acute toxicity** May be fatal if swallowed and enters airways.

Product Species Test Results

Gasoline 1-Tank Power Renew® - 15 fl oz

Acute

Oral ATEmix

668.44852941243323 mg/kg

Components Species Test Results

distillates (petroleum), hydrotreated light (CAS 64742-47-8)

Acute Dermal

LD50 Rat

> 2000 mg/kg

Inhalation

LC50 Rat > 5 mg/l, 4 hours

Oral

LD50 Rat > 5000 mg/kg, 2.5 hours

**Skin corrosion/irritation** Causes severe skin burns and eye damage.

Serious eye damage/eye

irritation

Causes serious eye damage.

Respiratory or skin sensitization

**Respiratory sensitization** Not a respiratory sensitizer.

Skin sensitization May cause an allergic skin reaction.

Germ cell mutagenicity Suspected of causing genetic defects.

Carcinogenicity Suspected of causing cancer.

IARC Monographs. Overall Evaluation of Carcinogenicity

Not listed.

#### OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

#### US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

This product is not expected to cause reproductive or developmental effects. Reproductive toxicity

Specific target organ toxicity -

Not classified.

single exposure

Specific target organ toxicity -

repeated exposure

Not classified.

**Aspiration hazard** May be fatal if swallowed and enters airways.

**Chronic effects** Prolonged inhalation may be harmful.

## 12. Ecological information

**Ecotoxicity** Toxic to aquatic life with long lasting effects.

Components		Species	Test Results
distillates (petroleum)	, hydrodesulfurized	middle (CAS 64742-80-9)	
Aquatic			
Crustacea	EC50	Water flea (Daphnia pulex)	2.7 - 5.1 mg/l, 48 hours
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	8.8 mg/l, 96 hours
			8.8 mg/l, 96 hours
distillates (petroleum)	, hydrotreated light (	(CAS 64742-47-8)	
Aquatic			
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	2.9 mg/l, 96 hours
polyether amine			
Aquatic			
Acute			
Crustacea	EC50	Crustacea	> 120 mg/l, 48 hours

Persistence and degradability

No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential

Fish

Partition coefficient n-octanol / water (log Kow)

distillates (petroleum), hydrodesulfurized middle 3.3 - 6

LC50

Mobility in soil No data available.

Other adverse effects The product contains volatile organic compounds which have a photochemical ozone creation

potential.

## 13. Disposal considerations

This product is not a RCRA hazardous waste (See 40 CFR Part 261.20 - 261.33). Empty **Disposal instructions** 

> containers may be recycled. Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose in accordance with all

> 100 mg/l, 96 hours

applicable regulations.

Fish

Hazardous waste code Not regulated.

Since emptied containers may retain product residue, follow label warnings even after container is Contaminated packaging

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

## 14. Transport information

DOT

**UN number** UN1760

**UN proper shipping name** 

Corrosive liquids, n.o.s. (polyether amine), Limited Quantity

Transport hazard class(es)

Class 8 Subsidiary risk

Material name: Gasoline 1-Tank Power Renew® - 15 fl oz

No. 05815 (Item# 1003859) Version #: 02 Revision date: 03-11-2020 Issue date: 08-13-2019

Packing group

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Special provisions B2, IB2, T11, TP2, TP27

Packaging exceptions154Packaging non bulk202Packaging bulk242

Other information

Passenger and cargo

aircraft

Forbidden

Cargo aircraft only

Forbidden

**IATA** 

UN number UN1760

UN proper shipping name

Corrosive liquid, n.o.s. (polyether amine)

Transport hazard class(es)

Class 8
Subsidiary risk Packing group II
ERG Code 8L

Special precautions for user Not packaged for shipment by air.

Other information

Passenger and cargo

•

Forbidden

aircraft

Cargo aircraft only Forbidden

**IMDG** 

UN number UN1760

UN proper shipping name CORROSIVE LIQUID, N.O.S. (polyether amine), Limited Quantity

Transport hazard class(es)

Class 8
Subsidiary risk Packing group ||


**Environmental hazards** 

**Marine pollutant** Yes, but exempt from the regulations.

EmS F-A, S-B

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

#### DOT: IMDG



## **IATA**



## 15. Regulatory information

**US federal regulations**This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

#### TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

**CERCLA Hazardous Substance List (40 CFR 302.4)** 

Not listed.

**CERCLA Hazardous Substances: Reportable quantity** 

Not listed.

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

#### Other federal regulations

#### Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

#### Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

**Food and Drug** 

Not regulated.

Administration (FDA)

#### Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

No (Exempt)

chemical

#### SARA 313 (TRI reporting)

Not regulated.

#### **US** state regulations

#### US. New Jersey Worker and Community Right-to-Know Act

distillates (petroleum), hydrodesulfurized middle (CAS 64742-80-9)

**US. Massachusetts RTK - Substance List** 

distillates (petroleum), hydrodesulfurized middle (CAS 64742-80-9)

#### US. Pennsylvania Worker and Community Right-to-Know Law

distillates (petroleum), hydrodesulfurized middle (CAS 64742-80-9) distillates (petroleum), hydrotreated light (CAS 64742-47-8)

**US. Rhode Island RTK** 

distillates (petroleum), hydrodesulfurized middle (CAS 64742-80-9) distillates (petroleum), hydrotreated light (CAS 64742-47-8)

#### **California Proposition 65**



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

## California Proposition 65 - CRT: Listed date/Carcinogenic substance

benzene (CAS 71-43-2) Listed: February 27, 1987 ethylbenzene (CAS 100-41-4) Listed: June 11, 2004 naphthalene (CAS 91-20-3) Listed: April 19, 2002

California Proposition 65 - CRT: Listed date/Developmental toxin

benzene (CAS 71-43-2) Listed: December 26, 1997 toluene (CAS 108-88-3) Listed: January 1, 1991

California Proposition 65 - CRT: Listed date/Male reproductive toxin

Listed: December 26, 1997 benzene (CAS 71-43-2)

## US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

distillates (petroleum), hydrodesulfurized middle (CAS 64742-80-9) distillates (petroleum), hydrotreated light (CAS 64742-47-8)

## Volatile organic compounds (VOC) regulations

**EPA** 

VOC content (40 CFR 100 %

51.100(s))

Consumer products Not regulated

(40 CFR 59, Subpt. C)

State

Consumer products Not regulated

VOC content (CA) 91 % VOC content (OTC) 91 %

#### **International Inventories**

Country(s) or region

		, ( <b>,</b> )
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances	Yes

Taiwan Chemical Substance Inventory (TCSI)
United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

Inventory name

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing

## 16. Other information, including date of preparation or last revision

Issue date08-13-2019Revision date03-11-2020Prepared byAllison Yoon

Version # 02

Further information CRC # 1750773

**Disclaimer** The information contained in this document applies to this specific material as supplied. It may not

be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC's knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety

professional, or CRC Industries, Inc..

**Revision information** Product and Company Identification: Product Registration Numbers

Hazard(s) identification: Hazard statement Hazard(s) identification: Prevention Hazard(s) identification: Response

Composition / Information on Ingredients: Disclosure Overrides

Physical & Chemical Properties: Multiple Properties Toxicological Information: Toxicological Data

Ecological Information: Ecotoxicity

Transport Information: Material Transportation Information

GHS: Classification

On inventory (yes/no)\*

Yes

A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s).

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).