



# SAFETY DATA SHEET

## 1. Identification

**Product identifier** Trans-X® Transmission Stop Leak & Tune Up - 15 fl oz

**Other means of identification**

**Product Code** No. 402015 (Item# 1006088)

**Recommended use** Transmission fluid additive

**Recommended restrictions** None known.

**Manufacturer/Importer/Supplier/Distributor information**

**Manufactured or sold by:**

**Company name** CRC Industries, Inc.

**Address** 885 Louis Dr.  
Warminster, PA 18974 US

**Telephone**

**General Information** 215-674-4300

**Technical Assistance** 800-521-3168

**Customer Service** 800-272-4620

**24-Hour Emergency  
(CHEMTREC)** 800-424-9300 (US)

**Website** [www.crcindustries.com](http://www.crcindustries.com)

## 2. Hazard(s) identification

**Physical hazards** Flammable liquids Category 2

**Health hazards** Serious eye damage/eye irritation Category 2A

Carcinogenicity Category 2

Reproductive toxicity Category 2

Specific target organ toxicity, repeated exposure Category 2

Aspiration hazard Category 1

**Environmental hazards** Hazardous to the aquatic environment, acute hazard Category 3

Hazardous to the aquatic environment, long-term hazard Category 3

**OSHA defined hazards** Not classified.

**Label elements**



**Signal word** Danger

**Hazard statement** Highly flammable liquid and vapor. May be fatal if swallowed and enters airways. Causes serious eye irritation. Suspected of causing cancer. Suspected of damaging fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure.

## Precautionary statement

### Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Use only outdoors or in a well-ventilated area. Maintain ventilation during use and until all vapors are gone. Do not breathe mist/vapors. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection.

### Response

If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If exposed or concerned: Get medical advice/attention. In case of fire: Do not use water jet as an extinguisher, as this will spread the fire.

### Storage

Store in a well-ventilated place. Keep cool. Store locked up.

### Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

### Hazard(s) not otherwise classified (HNOC)

None known.

### Supplemental information

None.

## 3. Composition/information on ingredients

### Mixtures

Chemical name	Common name and synonyms	CAS number	%
distillates (petroleum), hydrotreated heavy naphthenic		64742-52-5	70 - 80
isopropyl alcohol		67-63-0	10 - 20
xylene		1330-20-7	5 - 10
toluene		108-88-3	3 - 5
diacetone alcohol		123-42-2	1 - 3
ethylbenzene		100-41-4	1 - 3

Specific chemical identity and/or percentage of composition has been withheld as a trade secret.

## 4. First-aid measures

### Inhalation

Move to fresh air. Call a physician if symptoms develop or persist.

### Skin contact

Take off immediately all contaminated clothing. Rinse skin with water/shower. Get medical attention if irritation develops and persists.

### Eye contact

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

### Ingestion

Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

### Most important symptoms/effects, acute and delayed

Aspiration may cause pulmonary edema and pneumonitis. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Prolonged exposure may cause chronic effects.

### Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.

### General information

Take off all contaminated clothing immediately. IF exposed or concerned: Get medical advice/attention. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

## 5. Fire-fighting measures

### Suitable extinguishing media

Water fog. Alcohol resistant foam. Carbon dioxide (CO2). Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.

### Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

<b>Specific hazards arising from the chemical</b>	Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. This product is a poor conductor of electricity and can become electrostatically charged. If sufficient charge is accumulated, ignition of flammable mixtures can occur. Static electricity accumulation may be significantly increased by the presence of small quantities of water or other contaminants. Material will float and may ignite on surface of water. During fire, gases hazardous to health may be formed.
<b>Special protective equipment and precautions for firefighters</b>	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
<b>Fire-fighting equipment/instructions</b>	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk. Use standard firefighting procedures and consider the hazards of other involved materials.
<b>Specific methods</b>	Use standard firefighting procedures and consider the hazards of other involved materials.
<b>General fire hazards</b>	Highly flammable liquid and vapor.

## 6. Accidental release measures

<b>Personal precautions, protective equipment and emergency procedures</b>	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist/vapors. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Use appropriate containment to avoid environmental contamination. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
<b>Methods and materials for containment and cleaning up</b>	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools. This product is miscible in water. This material is classified as a water pollutant under the Clean Water Act and should be prevented from contaminating soil or from entering sewage and drainage systems which lead to waterways.  Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.  Never return spills to original containers for re-use. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.
<b>Environmental precautions</b>	Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. Use appropriate containment to avoid environmental contamination.

## 7. Handling and storage

<b>Precautions for safe handling</b>	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Minimize fire risks from flammable and combustible materials (including combustible dust and static accumulating liquids) or dangerous reactions with incompatible materials. Handling operations that can promote accumulation of static charges include but are not limited to: mixing, filtering, pumping at high flow rates, splash filling, creating mists or sprays, tank and container filling, tank cleaning, sampling, gauging, switch loading, vacuum truck operations. Take precautionary measures against static discharges. Use non-sparking tools and explosion-proof equipment. Do not breathe mist/vapors. Avoid contact with eyes. Avoid prolonged exposure. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices. For product usage instructions, see the product label.
<b>Conditions for safe storage, including any incompatibilities</b>	Keep away from heat, sparks and open flame. Eliminate sources of ignition. Avoid spark promoters. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

## 8. Exposure controls/personal protection

### Occupational exposure limits

#### US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
diacetone alcohol (CAS 123-42-2)	PEL	240 mg/m3	

**US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)**

Components	Type	Value	Form
distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	PEL	50 ppm	Mist.
		5 mg/m3	
ethylbenzene (CAS 100-41-4)	PEL	2000 mg/m3	
		500 ppm	
		435 mg/m3	
isopropyl alcohol (CAS 67-63-0)	PEL	100 ppm	
		980 mg/m3	
xylene (CAS 1330-20-7)	PEL	400 ppm	
		435 mg/m3	
		100 ppm	

**US. OSHA Table Z-2 (29 CFR 1910.1000)**

Components	Type	Value
toluene (CAS 108-88-3)	Ceiling	300 ppm
	TWA	200 ppm

**US. ACGIH Threshold Limit Values**

Components	Type	Value	Form
diacetone alcohol (CAS 123-42-2)	TWA	50 ppm	Inhalable fraction.
distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	TWA	5 mg/m3	
ethylbenzene (CAS 100-41-4)	TWA	20 ppm	
isopropyl alcohol (CAS 67-63-0)	STEL	400 ppm	
toluene (CAS 108-88-3)	TWA	200 ppm	
	TWA	20 ppm	
	STEL	150 ppm	
xylene (CAS 1330-20-7)	TWA	100 ppm	

**US. NIOSH: Pocket Guide to Chemical Hazards**

Components	Type	Value	Form
diacetone alcohol (CAS 123-42-2)	TWA	240 mg/m3	
distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	Ceiling	50 ppm	
		1800 mg/m3	
	STEL	10 mg/m3	
	TWA	5 mg/m3	
ethylbenzene (CAS 100-41-4)	STEL	545 mg/m3	Mist.
		125 ppm	

**US. NIOSH: Pocket Guide to Chemical Hazards**

Components	Type	Value	Form
isopropyl alcohol (CAS 67-63-0)	TWA	435 mg/m3	
		100 ppm	
	STEL	1225 mg/m3	
toluene (CAS 108-88-3)		500 ppm	
	TWA	980 mg/m3	
		400 ppm	
xylene (CAS 1330-20-7)	STEL	560 mg/m3	
		150 ppm	
	TWA	375 mg/m3	
		100 ppm	
	STEL	655 mg/m3	
		150 ppm	
	TWA	435 mg/m3	
		100 ppm	

**Biological limit values**
**ACGIH Biological Exposure Indices**

Components	Value	Determinant	Specimen	Sampling Time
ethylbenzene (CAS 100-41-4)	0.15 g/g	Sum of mandelic acid and phenylglyoxylic acid	Creatinine in urine	*
isopropyl alcohol (CAS 67-63-0)	40 mg/l	Acetone	Urine	*
toluene (CAS 108-88-3)	0.3 mg/g	o-Cresol, with hydrolysis	Creatinine in urine	*
	0.03 mg/l	Toluene	Urine	*
	0.02 mg/l	Toluene	Blood	*
xylene (CAS 1330-20-7)	1.5 g/g	Methylhippuric acids	Creatinine in urine	*

\* - For sampling details, please see the source document.

**Exposure guidelines**
**US - California OELs: Skin designation**

toluene (CAS 108-88-3)

Can be absorbed through the skin.

**US - Minnesota Haz Subs: Skin designation applies**

toluene (CAS 108-88-3)

Skin designation applies.

**Appropriate engineering controls**

Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower should be available when handling this product.

**Individual protection measures, such as personal protective equipment**
**Eye/face protection**

Wear safety glasses with side shields (or goggles).

**Skin protection**
**Hand protection**

Wear protective gloves such as: Neoprene. Nitrile.

**Other**

Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

**Respiratory protection**

If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to determine actual employee exposure levels.

<b>Thermal hazards</b>	Wear appropriate thermal protective clothing, when necessary.
<b>General hygiene considerations</b>	When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

## 9. Physical and chemical properties

### Appearance

<b>Physical state</b>	Liquid.
<b>Form</b>	Liquid.
<b>Color</b>	Red.
<b>Odor</b>	Mild petroleum.
<b>Odor threshold</b>	Not available.
<b>pH</b>	Not available.
<b>Melting point/freezing point</b>	-138.8 °F (-94.9 °C) estimated
<b>Initial boiling point and boiling range</b>	179.6 °F (82 °C) estimated
<b>Flash point</b>	61.0 °F (16.1 °C) Setaflash
<b>Evaporation rate</b>	Slow.
<b>Flammability (solid, gas)</b>	Not available.
<b>Upper/lower flammability or explosive limits</b>	
<b>Flammability limit - lower (%)</b>	1 % estimated
<b>Flammability limit - upper (%)</b>	13 % estimated
<b>Vapor pressure</b>	7.7 hPa estimated
<b>Vapor density</b>	> 1 (air = 1)
<b>Relative density</b>	0.87
<b>Solubility(ies)</b>	
<b>Solubility (water)</b>	Negligible.
<b>Partition coefficient (n-octanol/water)</b>	Not available.
<b>Auto-ignition temperature</b>	600 °F (315.6 °C) estimated
<b>Decomposition temperature</b>	Not available.
<b>Viscosity</b>	Not available.
<b>Percent volatile</b>	Not available.

## 10. Stability and reactivity

<b>Reactivity</b>	The product is stable and non-reactive under normal conditions of use, storage and transport.
<b>Chemical stability</b>	Material is stable under normal conditions.
<b>Possibility of hazardous reactions</b>	No dangerous reaction known under conditions of normal use.
<b>Conditions to avoid</b>	Avoid heat, sparks, open flames and other ignition sources. Contact with incompatible materials.
<b>Incompatible materials</b>	Strong acids. Strong oxidizing agents. Chlorine. Halogens. Isocyanates.
<b>Hazardous decomposition products</b>	Carbon oxides. Hydrocarbon fumes and smoke. Aldehydes.

## 11. Toxicological information

### Information on likely routes of exposure

<b>Inhalation</b>	Prolonged inhalation may be harmful.
<b>Skin contact</b>	Based on available data, the classification criteria are not met.
<b>Eye contact</b>	Causes serious eye irritation.
<b>Ingestion</b>	Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.

**Symptoms related to the physical, chemical and toxicological characteristics**

Aspiration may cause pulmonary edema and pneumonitis. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

**Information on toxicological effects**

**Acute toxicity** May be fatal if swallowed and enters airways.

Components	Species	Test Results
------------	---------	--------------

diacetone alcohol (CAS 123-42-2)

**Acute**

**Dermal**

LD50 Rabbit 14.5 ml/kg

**Oral**

LD50 Rat 4 g/kg

distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)

**Acute**

**Dermal**

LD50 Rabbit > 2000 mg/kg

**Oral**

LD50 Rat > 5000 mg/kg

**Skin corrosion/irritation** Prolonged skin contact may cause temporary irritation.

**Serious eye damage/eye irritation** Causes serious eye irritation.

**Respiratory or skin sensitization**

**Respiratory sensitization** Not a respiratory sensitizer.

**Skin sensitization** This product is not expected to cause skin sensitization.

**Germ cell mutagenicity** No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

**Carcinogenicity** Suspected of causing cancer.

**IARC Monographs. Overall Evaluation of Carcinogenicity**

ethylbenzene (CAS 100-41-4) 2B Possibly carcinogenic to humans.  
toluene (CAS 108-88-3) 3 Not classifiable as to carcinogenicity to humans.  
xylene (CAS 1330-20-7) 3 Not classifiable as to carcinogenicity to humans.

**OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)**

Not listed.

**US. National Toxicology Program (NTP) Report on Carcinogens**

Not listed.

**Reproductive toxicity** Components in this product have been shown to cause birth defects and reproductive disorders in laboratory animals. Suspected of damaging fertility or the unborn child.

**Specific target organ toxicity - single exposure** Not classified.

**Specific target organ toxicity - repeated exposure** May cause damage to organs through prolonged or repeated exposure.

**Aspiration hazard** May be fatal if swallowed and enters airways.

**Chronic effects** Prolonged inhalation may be harmful. May cause damage to organs through prolonged or repeated exposure. Prolonged exposure may cause chronic effects.

---

## 12. Ecological information

**Ecotoxicity** Harmful to aquatic life with long lasting effects.

Components	Species	Test Results
------------	---------	--------------

toluene (CAS 108-88-3)

**Acute**


Other EC50 Pseudokirchnerella subcapitata 433 mg/l, 96 hours  
12.5 mg/l, 72 hours

Components	Species	Test Results
<b>Aquatic</b>		
<i>Acute</i>		
Fish	LC50 Coho salmon,silver salmon (Oncorhynchus kisutch)	5.5 mg/l, 96 hours
<b>Persistence and degradability</b>	No data is available on the degradability of any ingredients in the mixture.	
<b>Bioaccumulative potential</b>		
<b>Partition coefficient n-octanol / water (log Kow)</b>		
diacetone alcohol		-0.098
ethylbenzene		3.15
isopropyl alcohol		0.05
toluene		2.73
<b>Bioconcentration factor (BCF)</b>		
ethylbenzene		1
toluene		90
xylene		23.99
<b>Mobility in soil</b>	No data available.	
<b>Other adverse effects</b>	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.	
<b>13. Disposal considerations</b>		
<b>Disposal instructions</b>	If discarded, this product is considered a RCRA ignitable waste, D001. Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose in accordance with all applicable regulations.	
<b>Hazardous waste code</b>	D001: Waste Flammable material with a flash point <140 F	
<b>Contaminated packaging</b>	Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.	
<b>14. Transport information</b>		
<b>DOT</b>		
<b>UN number</b>	UN1993	
<b>UN proper shipping name</b>	Flammable liquids, n.o.s. (isopropyl alcohol RQ = 789 LBS, xylene RQ = 1808 LBS), Limited Quantity	
<b>Transport hazard class(es)</b>		
<b>Class</b>	3	
<b>Subsidiary risk</b>	-	
<b>Label(s)</b>	3	
<b>Packing group</b>	II	
<b>Special precautions for user</b>	Read safety instructions, SDS and emergency procedures before handling.	
<b>Special provisions</b>	IB2, T7, TP1, TP8, TP28	
<b>Packaging exceptions</b>	150	
<b>Packaging non bulk</b>	202	
<b>Packaging bulk</b>	242	
<b>IATA</b>		
<b>UN number</b>	UN1993	
<b>UN proper shipping name</b>	Flammable liquid, n.o.s. (isopropyl alcohol, xylene)	
<b>Transport hazard class(es)</b>		
<b>Class</b>	3	
<b>Subsidiary risk</b>	-	
<b>Packing group</b>	II	
<b>ERG Code</b>	3H	
<b>Special precautions for user</b>	Read safety instructions, SDS and emergency procedures before handling.	
<b>Other information</b>		
<b>Passenger and cargo aircraft</b>	Allowed with restrictions.	
<b>Cargo aircraft only</b>	Allowed with restrictions.	
<b>IMDG</b>		
<b>UN number</b>	UN1993	



**UN proper shipping name** FLAMMABLE LIQUID, N.O.S. (isopropyl alcohol, xylene), Limited Quantity  
**Transport hazard class(es)**  
**Class** 3  
**Subsidiary risk** -  
**Packing group** II  
**Environmental hazards**  
**Marine pollutant** No.  
**EmS** F-E, S-E  
**Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.

DOT; IMDG



IATA



## 15. Regulatory information

**US federal regulations** This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

### TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

### SARA 304 Emergency release notification

Not regulated.

### OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

### CERCLA Hazardous Substance List (40 CFR 302.4)

ethylbenzene (CAS 100-41-4)

toluene (CAS 108-88-3)

xylene (CAS 1330-20-7)

### CERCLA Hazardous Substances: Reportable quantity

ethylbenzene (CAS 100-41-4) 1000 LBS

toluene (CAS 108-88-3) 1000 LBS

xylene (CAS 1330-20-7) 100 LBS

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

### Other federal regulations

#### Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

ethylbenzene (CAS 100-41-4)

toluene (CAS 108-88-3)

xylene (CAS 1330-20-7)

#### Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

**Safe Drinking Water Act (SDWA)** Contains component(s) regulated under the Safe Drinking Water Act.

**Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number**

toluene (CAS 108-88-3) 6594

**Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))**

toluene (CAS 108-88-3) 35 %WV

**DEA Exempt Chemical Mixtures Code Number**

toluene (CAS 108-88-3) 594

**FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace**

isopropyl alcohol (CAS 67-63-0) Low priority

**Food and Drug Administration (FDA)** Not regulated.

**Superfund Amendments and Reauthorization Act of 1986 (SARA)**

**Classified hazard categories** Flammable (gases, aerosols, liquids, or solids)  
Serious eye damage or eye irritation  
Carcinogenicity  
Reproductive toxicity  
Specific target organ toxicity (single or repeated exposure)  
Aspiration hazard

**SARA 302 Extremely hazardous substance**

Not listed.

**SARA 311/312 Hazardous chemical** Yes

**SARA 313 (TRI reporting)**

Chemical name	CAS number	% by wt.
ethylbenzene	100-41-4	1 - 3
toluene	108-88-3	3 - 5
xylene	1330-20-7	5 - 10

**US state regulations**

**US. New Jersey Worker and Community Right-to-Know Act**

diacetone alcohol (CAS 123-42-2)  
ethylbenzene (CAS 100-41-4)  
isopropyl alcohol (CAS 67-63-0)  
toluene (CAS 108-88-3)  
xylene (CAS 1330-20-7)

**US. Massachusetts RTK - Substance List**

diacetone alcohol (CAS 123-42-2)  
ethylbenzene (CAS 100-41-4)  
isopropyl alcohol (CAS 67-63-0)  
toluene (CAS 108-88-3)  
xylene (CAS 1330-20-7)

**US. Pennsylvania Worker and Community Right-to-Know Law**

diacetone alcohol (CAS 123-42-2)  
ethylbenzene (CAS 100-41-4)  
isopropyl alcohol (CAS 67-63-0)  
toluene (CAS 108-88-3)  
xylene (CAS 1330-20-7)

**US. Rhode Island RTK**

diacetone alcohol (CAS 123-42-2)  
distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)  
ethylbenzene (CAS 100-41-4)  
isopropyl alcohol (CAS 67-63-0)  
toluene (CAS 108-88-3)  
xylene (CAS 1330-20-7)

**California Proposition 65**



**WARNING:** Cancer and Reproductive Harm - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

**California Proposition 65 - CRT: Listed date/Carcinogenic substance**

benzene (CAS 71-43-2)	Listed: February 27, 1987
cumene (CAS 98-82-8)	Listed: April 6, 2010
ethylbenzene (CAS 100-41-4)	Listed: June 11, 2004
naphthalene (CAS 91-20-3)	Listed: April 19, 2002

**California Proposition 65 - CRT: Listed date/Developmental toxin**

benzene (CAS 71-43-2)	Listed: December 26, 1997
mercury (CAS 7439-97-6)	Listed: July 1, 1990
methanol (CAS 67-56-1)	Listed: March 16, 2012
toluene (CAS 108-88-3)	Listed: January 1, 1991

**California Proposition 65 - CRT: Listed date/Male reproductive toxin**

benzene (CAS 71-43-2)	Listed: December 26, 1997
-----------------------	---------------------------

**US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))**

distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)
ethylbenzene (CAS 100-41-4)
isopropyl alcohol (CAS 67-63-0)
toluene (CAS 108-88-3)
xylene (CAS 1330-20-7)

**Volatile organic compounds (VOC) regulations****EPA**

<b>VOC content (40 CFR 51.100(s))</b>	99.9 %
<b>Consumer products (40 CFR 59, Subpt. C)</b>	Not regulated

**State**

<b>Consumer products</b>	Not regulated
<b>VOC content (CA)</b>	23.8 %
<b>VOC content (OTC)</b>	23.8 %

**International Inventories**

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Industrial Chemicals (AICIS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

**16. Other information, including date of preparation or last revision**

<b>Issue date</b>	05-11-2021
<b>Prepared by</b>	Allison Yoon
<b>Version #</b>	01
<b>Further information</b>	CRC # 901/1002890

**Disclaimer**

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC's knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety professional, or CRC Industries, Inc..

**Revision information**

Product and Company Identification: Alternate Trade Names  
Hazard(s) identification: Prevention  
Physical & Chemical Properties: Multiple Properties  
Toxicological Information: Toxicological Data  
Ecological Information: Ecotoxicity  
GHS: Qualifiers