

SAFETY DATA SHEET

1. Identification

1. Identification		
Product identifier	Chlor-Free® Degreaser - 14 oz	
Other means of identification		
Product Code	No. 03185 (Item# 1003441)	
Recommended use	General purpose degreaser	
Recommended restrictions	None known.	
Manufacturer/Importer/Supplier	/Distributor information	
Manufactured or sold by:		
Company name	CRC Industries, Inc.	
Address	885 Louis Dr.	
	Warminster, PA 18974 US	
Telephone		
General Information	215-674-4300	
Technical Assistance	800-521-3168	
Customer Service	800-272-4620	
24-Hour Emergency (CHEMTREC)	800-424-9300 (US)	
Website	www.crcindustries.com	
2. Hazard(s) identification	1	
Physical hazards	Flammable aerosols	Category 1
	Gases under pressure	Compressed gas
Health hazards	Skin corrosion/irritation	Category 2
	Serious eye damage/eye irritation	Category 2A
	Reproductive toxicity	Category 2
	Specific target organ toxicity, single exposure	Category 3 narcotic effects
	Aspiration hazard	Category 1
Environmental hazards	Hazardous to the aquatic environment, acute hazard	Category 2
	Hazardous to the aquatic environment, long-term hazard	Category 2
OSHA defined hazards	Not classified.	
Label elements		
Signal word	Danger	
Hazard statement	Extremely flammable aerosol. Contains gas un	nder pressure; may explode if heated. May be fatal

swallowed and enters airways. Causes skin irritation. Causes serious eye irritation. May cause

drowsiness or dizziness. Suspected of damaging fertility or the unborn child.

Precautionary statement	
Prevention	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not apply while equipment is energized. Extinguish all flames, pilot lights, and heaters. Vapors will accumulate readily and may ignite. Use only outdoors or in a well-ventilated area. Maintain ventilation during use and until all vapors are gone. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Avoid breathing mist/vapor. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection.
Response	If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If on skin: Wash with plenty of water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If exposed or concerned: Get medical advice/attention.
Storage	Store in a well-ventilated place. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Exposure to high temperature may cause can to burst.
Disposal	Dispose of contents/container in accordance with local/regional/national regulations.
Hazard(s) not otherwise classified (HNOC)	Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.
Supplemental information	None.

3. Composition/information on ingredients

Mixtures

media

Chemical name	Common name and synonyms	CAS number	%
acetone		67-64-1	40 - 50
naphtha (petroleum), hydrotreated light		64742-49-0	40 - 50
carbon dioxide		124-38-9	5 - 10
n-hexane		110-54-3	0.1 - 1

Specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures	
Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison center or doctor/physician if you feel unwell.
Skin contact	Remove contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Ingestion	Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.
Most important symptoms/effects, acute and delayed	Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	IF exposed or concerned: Get medical advice/attention. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.
5. Fire-fighting measures	
Suitable extinguishing media	Water fog. Alcohol resistant foam. Carbon dioxide (CO2). Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.
Unsuitable extinguishing	Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical	Contents under pressure. Pressurized container may rupture when exposed to heat or flame. This product is a poor conductor of electricity and can become electrostatically charged. If sufficient charge is accumulated, ignition of flammable mixtures can occur. Static electricity accumulation may be significantly increased by the presence of small quantities of water or other contaminants. Material will float and may ignite on surface of water. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
Fire-fighting equipment/instructions	In case of fire: Stop leak if safe to do so. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up.
General fire hazards	Extremely flammable aerosol. Contents under pressure. Pressurized container may rupture when exposed to heat or flame.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Remove all possible sources of ignition in the surrounding area. Keep out of low areas. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapor. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Use appropriate containment to avoid environmental contamination. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. This material is classified as a water pollutant under the Clean Water Act and should be prevented from contaminating soil or from entering sewage and drainage systems which lead to waterways. Stop the flow of material, if this is without risk. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. Use appropriate containment to avoid environmental contamination.
7. Handling and storage	
Precautions for safe handling	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Minimize fire risks from flammable and combustible materials (including combustible dust and static accumulating liquids) or dangerous reactions with incompatible materials. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Use caution around energized equipment. The metal container will conduct electricity if it contacts a live source. This may result in injury to the user from electrical shock and/or flash fire. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices. For product usage instructions, see the product label.
Conditions for safe storage,	Level 3 Aerosol.
including any incompatibilities	Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50 °C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Avoid spark promoters. These alone may be insufficient to remove static electricity. Store in tightly closed container. Store in a well-ventilated place. Stored containers should be periodically checked for general condition and leakage. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)			
Components	Туре	Value	
acetone (CAS 67-64-1)	PEL	2400 mg/m3	
		1000 ppm	

Components		Туре		```	/alue
carbon dioxide (CAS 124-38-9)		PEL		ę	0000 mg/m3
				5	5000 ppm
naphtha (petroleum), hydrotreated light (CAS 64742-49-0)		PEL		4	400 mg/m3
				1	00 ppm
n-hexane (CAS 110-54-3)		PEL		1	800 mg/m3
				5	500 ppm
US. ACGIH Threshold Lin	nit Values				
Components		Туре		١	/alue
acetone (CAS 67-64-1)		STEL		5	500 ppm
		TWA		2	250 ppm
carbon dioxide (CAS 124-38-9)		STEL		3	30000 ppm
		TWA		5	5000 ppm
n-hexane (CAS 110-54-3)		STEL		1	000 ppm
		TWA		5	50 ppm
US. NIOSH: Pocket Guide	to Chemical Ha				
Components		Туре		<u>۱</u>	/alue
acetone (CAS 67-64-1)		TWA		5	590 mg/m3
				2	250 ppm
carbon dioxide (CAS 124-38-9)		STEL			54000 mg/m3
					30000 ppm
		TWA			0000 mg/m3
					5000 ppm
naphtha (petroleum), hydrotreated light (CAS 64742-49-0)		TWA		4	100 mg/m3
				1	00 ppm
n-hexane (CAS 110-54-3)		Ceilin	g	1	800 mg/m3
				5	510 ppm
		TWA		1	80 mg/m3
				5	50 ppm
ogical limit values					
ACGIH Biological Exposu					
Components	Value		Determinant	Specimen	Sampling Time
acetone (CAS 67-64-1)	25 mg/l		Acetone	Urine	*
n-hexane (CAS 110-54-3)	0.5 mg/l		2,5-Hexanedio ne, without hydrolysis	Urine	*
* - For sampling details, ple	ease see the sou	rce docu	ment.		
osure guidelines					
US - California OELs: Ski	-				
n-hexane (CAS 110-54	1-3)		Can be	absorbed thro	ough the skin.

US ACGIH Threshold Limit V	alues: Skin designation			
n-hexane (CAS 110-54-3)	Danger of cutaneous absorption			
Appropriate engineering controls	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower should be available when handling this product.			
Individual protection measures,	such as personal protective equipment			
Eye/face protection	Wear safety glasses with side shields (or goggles).			
Skin protection				
Hand protection	Wear protective gloves such as: Nitrile. Polyvinyl chloride (PVC). Viton/butyl.			
Other	Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.			
Respiratory protection	If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to determine actual employee exposure levels.			
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.			
General hygiene considerations	When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.			

9. Physical and chemical properties

-	
Appearance	
Physical state	Liquid.
Form	Aerosol.
Color	Colorless.
Odor	Solvent.
Odor threshold	Not available.
рН	Not available.
Melting point/freezing point	-139.6 °F (-95.4 °C) estimated
Initial boiling point and boiling range	123.8 °F (51 °C) estimated
Flash point	< 0 °F (< -17.8 °C) estimated
Evaporation rate	Fast.
Flammability (solid, gas)	Not available.
Upper/lower flammability or exp	losive limits
Flammability limit - lower (%)	1.2 % estimated
Flammability limit - upper (%)	14.3 % estimated
Vapor pressure	6825 hPa estimated
Vapor density	> 1 (air = 1)
Relative density	0.77 estimated
Solubility(ies)	
Solubility (water)	Negligible.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	446 °F (230 °C) estimated
Decomposition temperature	Not available.
Viscosity	Not available.
Percent volatile	92.5 %

10. Stability and reactivity

The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Heat, flames and sparks. Contact with incompatible materials.
Incompatible materials	Acids. Strong oxidizing agents. Aluminum.
Hazardous decomposition products	Carbon oxides. Sulfur oxides. Aldehydes.

11. Toxicological information

Information on likely routes of exposure

Inhalation	May cause drowsiness and dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be harmful.		
Skin contact	Causes skin irritation.		
Eye contact	Causes serious eye irritation.		
Ingestion	Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.		
Symptoms related to the physical, chemical and toxicological characteristics	Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain.		
Information on toxicological effe	ects		
Acute toxicity	May be fatal if swallowed and enters airways.		
Components	Species	Test Results	
acetone (CAS 67-64-1)			
Acute			
Dermal		00000 //	
LD50	Rabbit	20000 mg/kg	
Oral LD50	Rat	5900 ma/ka	
		5800 mg/kg	
naphtha (petroleum), hydrotreated	light (CAS 64742-49-0)		
<u>Acute</u> Dermal			
LD50	Rat	> 2000 mg/kg	
Inhalation		0.0	
Vapor			
LC50	Rat	> 5.2 mg/l, 4 hours	
Oral			
LD50	Rat	> 5000 mg/kg	
n-hexane (CAS 110-54-3)			
Acute			
Dermal			
LD50	Rabbit	> 1300 mg/kg	
Oral	Det	15940	
LD50	Rat	15840 mg/kg	
Skin corrosion/irritation	Causes skin irritation.		
Serious eye damage/eye irritation	Causes serious eye irritation.		
Respiratory or skin sensitization	n		
Respiratory sensitization	Not a respiratory sensitizer.		
Skin sensitization	This product is not expected to cause skin sensitization.		
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.		
Carcinogenicity	Not classifiable as to carcinogenicity to humans.		

IARC Monographs. Overall E	valuation	of Carcinogenicity			
Not listed.					
OSHA Specifically Regulated Not listed.	d Substan	ces (29 CFR 1910.10	01-1053)		
Not listed. US. National Toxicology Pro Not listed.	gram (NTF	P) Report on Carcino	gens		
Reproductive toxicity	Suspected of damaging fertility or the unborn child.				
Specific target organ toxicity - single exposure	May cause drowsiness and dizziness.				
Specific target organ toxicity - repeated exposure	Not classified.				
Aspiration hazard	May be fatal if swallowed and enters airways.				
Chronic effects	Prolonge	Prolonged inhalation may be harmful.			
12. Ecological information	1				
Ecotoxicity	Toxic to a	aquatic life with long la	sting effects.		
Components		Species		Test Results	
n-hexane (CAS 110-54-3)					
Aquatic					
Acute					
Fish	LC50	Fathead minnov	w (Pimephales pron	nelas) 2500 μg/l, 96 hours	
Persistence and degradability	No data i	s available on the deg	radability of any ing	redients in the mixture.	
Bioaccumulative potential	No data a	available.			
Partition coefficient n-octand acetone	ol / water ((log Kow)	-0.24		
n-hexane			3.9		
Bioconcentration factor (BC					
naphtha (petroleum), hydrotrea n-hexane	ated light		10 - 2500 501.187		
Mobility in soil	No data a	available.			
Other adverse effects				e depletion, photochemical ozone creation ential) are expected from this component.	
13. Disposal consideration	าร				
Disposal instructions	This material and its container must be disposed of as hazardous waste. Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Dispose in accordance with all applicable regulations.				
Hazardous waste code	D001: Waste Flammable material with a flash point <140 F F003: Waste Non-halogenated Solvent - Spent Non-halogenated Solvent				
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.				
14. Transport information					
DOT					
UN number	UN1950				
UN proper shipping name	Aerosols, flammable, Limited Quantity				
Transport hazard class(es) Class	2.1				
Subsidiary risk	Z. I -				
Label(s)	2.1				
Packing group	-				
Special precautions for user		ety instructions, SDS	and emergency pro	cedures before handling.	
Special provisions	N82				
Packaging exceptions Packaging non bulk	306 None				
Packaging holi bulk	None				


None

Packaging bulk

Other information	
Passenger and cargo aircraft	Allowed with restrictions.
Cargo aircraft only	Allowed with restrictions.
IATA	Allowed with restrictions.
UN number	UN1950
UN proper shipping name Transport hazard class(es)	Aerosols, flammable, Limited Quantity
Class	2.1
Subsidiary risk	-
Packing group	-
ERG Code	10L
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Other information	
Passenger and cargo aircraft	Allowed with restrictions.
Cargo aircraft only	Allowed with restrictions.
IMDG	
UN number	UN1950
UN proper shipping name	AEROSOLS, Limited Quantity
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Packing group	-
Environmental hazards	
Marine pollutant	Yes, but exempt from the regulations.
EmS	F-D, S-U
Special precautions for user	Read safety instructions SDS and emergency procedures before handling

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.





15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated. SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053) Not listed.					
CERCLA Hazardous Substance List (40 CFR 302.4)					
	acetone (CAS 67-64-1)				
	CERCLA Hazardous Substances: Reportable quantity				
acetone (CAS 67-64	,	5000 LBS			
Spills or releases resultin Response Center (800-42			Q require immediate notification ng Committee.	to the National	
Other federal regulations					
Clean Air Act (CAA) Section		lutants (HAPs) List			
n-hexane (CAS 110-54-3 Clean Air Act (CAA) Section	,	ase Prevention (40 C	CFR 68.130)		
Not regulated.					
Safe Drinking Water Act (SDWA)	Not regulated.				
Drug Enforcement Adm Chemical Code Number		, Essential Chemica	lls (21 CFR 1310.02(b) and 131	0.04(f)(2) and	
acetone (CAS 67-64		6532			
•		-	cal Mixtures (21 CFR 1310.12(c		
acetone (CAS 67-64	,	35 %WV			
DEA Exempt Chemical I acetone (CAS 67-64-		6532			
	,		vor Manufacturing Workplace		
acetone (CAS 67-64		Low priority	5		
Food and Drug Administration (FDA)	Not regulated.				
Superfund Amendments and Re	authorization Act of 198	36 (SARA)			
Classified hazard	Flammable (gases, aer		ls)		
categories	Gas under pressure Skin corrosion or irritati Serious eye damage or Reproductive toxicity Specific target organ to Aspiration hazard Hazard not otherwise c	on eye irritation xicity (single or repea			
SARA 302 Extremely hazard					
Not listed.	Vaa				
SARA 311/312 Hazardous chemical	Yes				
SARA 313 (TRI reporting)					
Chemical name		CAS number	% by wt.		
n-hexane		110-54-3	0.1 - 1		
US state regulations					
(a))	nemicals List. Safer Cor	isumer Products Re	gulations (Cal. Code Regs, tit.	22, 69502.3, subd.	
acetone (CAS 67-64-1) naphtha (petroleum), hyd n-hexane (CAS 110-54-3		2-49-0)			
US. New Jersey Worker and		now Act			
acetone (CAS 67-64-1) carbon dioxide (CAS 124 naphtha (petroleum), hyd n-hexane (CAS 110-54-3	rotreated light (CAS 6474	2-49-0)			
US. Massachusetts RTK - S					
acetone (CAS 67-64-1) carbon dioxide (CAS 124 naphtha (petroleum), hyd n-hexane (CAS 110-54-3	rotreated light (CAS 6474	12-49-0)			
	/				

US. Pennsylvania Worker and Community Right-to-Know Law

acetone (CAS 67-64-1) carbon dioxide (CAS 124-38-9) naphtha (petroleum), hydrotreated light (CAS 64742-49-0) n-hexane (CAS 110-54-3)

US. Rhode Island RTK

acetone (CAS 67-64-1) carbon dioxide (CAS 124-38-9) naphtha (petroleum), hydrotreated light (CAS 64742-49-0) n-hexane (CAS 110-54-3)

California Proposition 65



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

California Proposition 65 - CRT: Listed date/Carcinogenic substance acetaldehyde (CAS 75-07-0) Listed: April 1, 1988

acetaidenyde (CAS benzene (CAS 71-43 cumene (CAS 98-82 ethylbenzene (CAS California Proposition 6	B-2) Listed: February 27, 1987 -8) Listed: April 6, 2010		
benzene (CAS 71-43 methanol (CAS 67-5 toluene (CAS 108-88	B-2) Listed: December 26, 1997 6-1) Listed: March 16, 2012		
benzene (CAS 71-43 n-hexane (CAS 110-	,		
Volatile organic compounds (VC EPA	DC) regulations		
VOC content (40 CFR 51.100(s))	46.3 %		
Consumer products (40 CFR 59, Subpt. C)	Not regulated		
State			
Consumer products	This product is regulated as a General Purpose Degreaser (ae to be sold for use in California, Colorado, Connecticut, Delawa York, Rhode Island, and the following counties in Utah: Box E Tooele, Utah, and Weber. This product is compliant in all other	re, Maryland, New Hampshire, New Ider, Cache, Davis, Salt Lake,	
VOC content (CA)	46.3 %		
VOC content (OTC)	46.3 %		
International Inventories			
Country(s) or region	Inventory name	On inventory (yes/no)*	
Australia	Australian Inventory of Industrial Chemicals (AICIS)	Yes	
Canada	Domestic Substances List (DSL)	Yes	
Canada	Non-Domestic Substances List (NDSL)	No	
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes	
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)		
Europe	European List of Notified Chemical Substances (ELINCS)	No	
Japan	Inventory of Existing and New Chemical Substances (ENCS)		
Korea	Existing Chemicals List (ECL)		
New Zealand	New Zealand Inventory	Yes	
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes	
Taiwan	Taiwan Chemical Substance Inventory (TCSI)		
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes	

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

	G
Issue date	12-31-2019
Revision date	12-21-2021
Prepared by	Danica Fulmer
Version #	03
Further information	CRC # 463D-E/1002463-1008113
Disclaimer	The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC's knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety professional, or CRC Industries, Inc
Revision information	Product and Company Identification: Product and Company Identification Hazard(s) identification: Prevention Composition / Information on Ingredients: Component Summary Accidental release measures: Methods and materials for containment and cleaning up Physical & Chemical Properties: Multiple Properties Stability and reactivity: Hazardous decomposition products Ecological information: Bioaccumulative potential Transport Information: Proper Shipping Name/Packing Group Regulatory information: Consumer products