CR@

SAFETY DATA SHEET

1. Identification

Product identifier Brakleen® Brake Parts Cleaner - 14 oz

Other means of identification

Product Code No. 05088 (Item# 1003704)

Recommended use Brake parts cleaner

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufactured or sold by:

Company name CRC Industries, Inc.

Address 885 Louis Dr.

Warminster, PA 18974 US

Telephone

 General Information
 215-674-4300

 Technical Assistance
 800-521-3168

 Customer Service
 800-272-4620

 24-Hour Emergency
 800-424-9300 (US)

(CHEMTREC)

Website www.crcindustries.com

2. Hazard(s) identification

Physical hazards Flammable aerosols Category 1

Gases under pressure Compressed gas

Health hazards Skin corrosion/irritation Category 2

Serious eye damage/eye irritation Category 2A

Specific target organ toxicity, single exposure Category 3 narcotic effects

Aspiration hazard Category 1

Environmental hazards Hazardous to the aquatic environment, acute

hazard

Hazardous to the aquatic environment, Category 1

long-term hazard

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Extremely flammable aerosol. Contains gas under pressure; may explode if heated. May be fatal if

swallowed and enters airways. Causes skin irritation. Causes serious eye irritation. May cause

Category 1

drowsiness or dizziness.

Precautionary statement

Prevention

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not apply while equipment is energized. Extinguish all flames, pilot lights, and heaters. Vapors will accumulate readily and may ignite. Use only outdoors or in a well-ventilated area. Maintain ventilation during use and until all vapors are gone. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Avoid breathing mist/vapors. Wash thoroughly after handling. Wear eye protection/face protection. Wear protective gloves.

Material name: Brakleen® Brake Parts Cleaner - 14 oz No. 05088 (Item# 1003704) Version #: 01 Issue date: 12-16-2021

If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If in eyes: Rinse Response

cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If on skin: Wash with plenty of water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. If inhaled: Remove person to fresh air and keep comfortable for

breathing. Call a poison center/doctor if you feel unwell.

Storage Protect from sunlight. Store in a well-ventilated place. Keep container tightly closed. Store locked

up. Do not expose to temperatures exceeding 50°C/122°F. Exposure to high temperature may

cause can to burst.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC)

Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.

Supplemental information

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
naphtha (petroleum), hydrotreated light		64742-49-0	40 - 50
n-heptane		142-82-5	20 - 30
heptane, branched, cyclic and linear		426260-76-6	10 - 20
isopropyl alcohol		67-63-0	5 - 10
carbon dioxide		124-38-9	3 - 5
solvent naphtha (petroleum), light aliph.		64742-89-8	3 - 5

Specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison Inhalation

center or doctor/physician if you feel unwell.

Remove contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs: Get Skin contact

medical advice/attention. Wash contaminated clothing before reuse.

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if Eye contact present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If Ingestion

vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

redness, swelling, and blurred vision. Skin irritation. May cause redness and pain.

Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness or dizziness.

Most important symptoms/effects, acute and

delayed Indication of immediate

medical attention and special treatment needed

General information

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing,

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Water fog. Foam. Carbon dioxide (CO2). Dry chemical powder, carbon dioxide, sand or earth may Suitable extinguishing media be used for small fires only.

Unsuitable extinguishing media

Specific hazards arising from

Do not use water jet as an extinguisher, as this will spread the fire.

the chemical

Contents under pressure. Pressurized container may rupture when exposed to heat or flame. This product is a poor conductor of electricity and can become electrostatically charged. If sufficient charge is accumulated, ignition of flammable mixtures can occur. Static electricity accumulation may be significantly increased by the presence of small quantities of water or other contaminants. Material will float and may ignite on surface of water. During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Material name: Brakleen® Brake Parts Cleaner - 14 oz

Fire-fighting equipment/instructions

In case of fire: Stop leak if safe to do so. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. Use standard firefighting procedures and consider the hazards of other involved materials. In the event of fire and/or explosion do not breathe fumes.

General fire hazards

Extremely flammable aerosol. Contents under pressure. Pressurized container may rupture when exposed to heat or flame.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Remove all possible sources of ignition in the surrounding area. Keep out of low areas. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapors. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Use appropriate containment to avoid environmental contamination. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Prevent product from entering drains. Stop the flow of material, if this is without risk. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. Use appropriate containment to avoid environmental contamination.

7. Handling and storage

Precautions for safe handling

Minimize fire risks from flammable and combustible materials (including combustible dust and static accumulating liquids) or dangerous reactions with incompatible materials. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Use caution around energized equipment. The metal container will conduct electricity if it contacts a live source. This may result in injury to the user from electrical shock and/or flash fire. Avoid breathing mist/vapors. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices. For product usage instructions, see the product label.

Conditions for safe storage, including any incompatibilities

Level 3 Aerosol.

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. Avoid spark promoters. These alone may be insufficient to remove static electricity. Store in tightly closed container. Store in a well-ventilated place. Stored containers should be periodically checked for general condition and leakage. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value	
carbon dioxide (CAS 124-38-9)	PEL	9000 mg/m3	
		5000 ppm	
isopropyl alcohol (CAS 67-63-0)	PEL	980 mg/m3	
		400 ppm	
naphtha (petroleum), hydrotreated light (CAS 64742-49-0)	PEL	400 mg/m3	

Material name: Brakleen® Brake Parts Cleaner - 14 oz

omponents	Туре	Value	
		100 ppm	
-heptane (CAS 142-82-5)	PEL	2000 mg/m3	
		500 ppm	
olvent naphtha	PEL	400 mg/m3	
petroleum), light aliph. CAS 64742-89-8)			
5A3 04742-09-0)		100 ppm	
S. ACGIH Threshold Limit Values			
omponents	Туре	Value	
arbon dioxide (CAS	STEL	30000 ppm	
24-38-9)	OTEL	обобо ррш	
	TWA	5000 ppm	
opropyl alcohol (CAS	STEL	400 ppm	
7-63-0)	TWA	200 nnm	
hantana (CAC 442 02 F)		200 ppm	
-heptane (CAS 142-82-5)	STEL	500 ppm	
	TWA	400 ppm	
S. NIOSH: Pocket Guide to Chemic omponents		Value	
<u> </u>	Туре		
arbon dioxide (CAS 24-38-9)	STEL	54000 mg/m3	
,		30000 ppm	
	TWA	9000 mg/m3	
		5000 ppm	
opropyl alcohol (CAS	STEL	1225 mg/m3	
7-63-0)			
		500 ppm	
	TWA	980 mg/m3	
		400 ppm	
aphtha (petroleum), ydrotreated light (CAS	TWA	400 mg/m3	
4742-49-0)			
		100 ppm	
-heptane (CAS 142-82-5)	Ceiling	1800 mg/m3	
		440 ppm	
	TWA	350 mg/m3	
		85 ppm	
olvent naphtha	TWA	400 mg/m3	
petroleum), light aliph. CAS 64742-89-8)			

Biol

ACGIH Biological Exposure Indices				
Components	Value	Determinant	Specimen	Sampling Time
isopropyl alcohol (CAS	40 mg/l	Acetone	Urine	*

^{* -} For sampling details, please see the source document.

Appropriate engineering

controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear protective gloves such as: Laminate film. Other Wear appropriate chemical resistant clothing

Respiratory protection If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a

NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to

determine actual employee exposure levels.

Wear appropriate thermal protective clothing, when necessary. Thermal hazards

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state Liquid. **Form** Aerosol. Color Colorless. Odor Pleasant. **Odor threshold** Not available. pН Not available.

-132 °F (-91.1 °C) estimated Melting point/freezing point Initial boiling point and boiling

range

190 °F (87.8 °C) estimated

15.8 °F (-9.0 °C) estimated Flash point

Evaporation rate Fast.

Flammability (solid, gas) Not available. Upper/lower flammability or explosive limits

Flammability limit - lower

1 % estimated

(%)

Flammability limit - upper

13 % estimated

(%)

2729.9 hPa estimated Vapor pressure

Vapor density > 1 (Air = 1)Relative density 0.72 estimated

Solubility(ies)

Solubility (water) Slightly soluble. Partition coefficient Not available.

(n-octanol/water)

433 °F (222.8 °C) estimated **Auto-ignition temperature**

Not available. **Decomposition temperature Viscosity** Not available. Not available. Percent volatile

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous No dangerous reaction known under conditions of normal use.

reactions

Conditions to avoid Heat. Contact with incompatible materials.

Incompatible materials Acids. Strong oxidizing agents. Chlorine. Isocyanates.

Hazardous decomposition

products

Carbon oxides. Sulfur oxides.

11. Toxicological information

Information on likely routes of exposure

Inhalation May cause drowsiness or dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be

harmful.

Skin contact Causes skin irritation.

Eye contact Causes serious eye irritation.

Ingestion Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious

chemical pneumonia.

Symptoms related to the physical, chemical and toxicological characteristics

Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness or dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing,

redness, swelling, and blurred vision. Skin irritation. May cause redness and pain.

Information on toxicological effects

Acute toxicity May be fatal if swallowed and enters airways.

Components Species Test Results

heptane, branched, cyclic and linear (CAS 426260-76-6)

<u>Acute</u>

Dermal

LD50 Rabbit > 2000 mg/kg

Inhalation

LC50 Rat > 60 mg/l, 4 hours

Oral

LD50 Rat > 5000 mg/kg

naphtha (petroleum), hydrotreated light (CAS 64742-49-0)

Acute

Dermal

LD50 Rat > 2000 mg/kg

Inhalation

Vapor

LC50 Rat > 5.2 mg/l, 4 hours

Oral

LD50 Rat > 5000 mg/kg

n-heptane (CAS 142-82-5)

Acute

Dermal

LD50 Rabbit > 2000 mg/kg

Inhalation

Vapor

LC50 Rat > 73.5 mg/l, 4 hours

Oral

LD50 Rat > 5000 mg/kg

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye

irritation

Causes serious eye irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity Not classifiable as to carcinogenicity to humans.

IARC Monographs. Overall Evaluation of Carcinogenicity

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

This product is not expected to cause reproductive or developmental effects. Reproductive toxicity

Specific target organ toxicity -

single exposure

May cause drowsiness or dizziness.

Specific target organ toxicity -

repeated exposure

Not classified.

May be fatal if swallowed and enters airways. **Aspiration hazard**

Chronic effects Prolonged inhalation may be harmful.

12. Ecological information

Ecotoxicity Very toxic to aquatic life with long lasting effects.

Test Results Components **Species** n-heptane (CAS 142-82-5) Aquatic

Acute

Crustacea EC50 Water flea (Daphnia magna) > 10 mg/l, 24 hours

1.5 mg/l, 48 hours

Fish LC50 Freshwater fish 375 mg/l, 96 hours

> Goldfish (Carassius auratus) 4 mg/l, 24 hours

Persistence and degradability No data is available on the degradability of any ingredients in the mixture.

No data available. Bioaccumulative potential Partition coefficient n-octanol / water (log Kow)

isopropyl alcohol 0.05 4.66 n-heptane

Bioconcentration factor (BCF)

naphtha (petroleum), hydrotreated light 10 - 2500

Mobility in soil No data available.

Other adverse effects The product contains volatile organic compounds which have a photochemical ozone creation

potential.

13. Disposal considerations

If discarded, this product is considered a RCRA ignitable waste, D001. Empty container can be **Disposal instructions**

recycled. Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose in accordance

with all applicable regulations.

Hazardous waste code D001: Waste Flammable material with a flash point <140 F

Since emptied containers may retain product residue, follow label warnings even after container is Contaminated packaging

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

DOT

UN number UN1950

UN proper shipping name Transport hazard class(es) Aerosols, flammable, Limited Quantity

Class 2.1 Subsidiary risk 2.1 Label(s) Packing group

Material name: Brakleen® Brake Parts Cleaner - 14 oz

No. 05088 (Item# 1003704) Version #: 01 Issue date: 12-16-2021

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Special provisions N82 306 Packaging exceptions Packaging non bulk None Packaging bulk None

IATA

UN1950 **UN** number

UN proper shipping name Aerosols, flammable, Limited Quantity

Transport hazard class(es)

Class 2.1 Subsidiary risk Packing group 10L **ERG Code**

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo

Allowed with restrictions.

aircraft

Cargo aircraft only Allowed with restrictions.

IMDG

UN number UN1950

UN proper shipping name

AEROSOLS, Limited Quantity

Transport hazard class(es)

Class 2.1 Subsidiary risk Packing group


Environmental hazards

Marine pollutant Yes, but exempt from the regulations.

F-D, S-U **EmS**

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

DOT; IMDG



15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed

CERCLA Hazardous Substances: Reportable quantity

Not listed.

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Contains component(s) regulated under the Safe Drinking Water Act.

(SDWA)

FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace

isopropyl alcohol (CAS 67-63-0) Low priority

Food and Drug Not regulated.

Administration (FDA)

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Classified hazard Flammable (gases, aerosols, liquids, or solids)

Gas under pressure categories Skin corrosion or irritation

Serious eye damage or eye irritation

Specific target organ toxicity (single or repeated exposure)

Aspiration hazard

Hazard not otherwise classified (HNOC)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous Yes

chemical

SARA 313 (TRI reporting)

Not regulated.

US state regulations

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

isopropyl alcohol (CAS 67-63-0)

naphtha (petroleum), hydrotreated light (CAS 64742-49-0)

n-heptane (CAS 142-82-5)

solvent naphtha (petroleum), light aliph. (CAS 64742-89-8)

US. New Jersey Worker and Community Right-to-Know Act

carbon dioxide (CAS 124-38-9)

isopropyl alcohol (CAS 67-63-0)

naphtha (petroleum), hydrotreated light (CAS 64742-49-0)

n-heptane (CAS 142-82-5)

solvent naphtha (petroleum), light aliph. (CAS 64742-89-8)

US. Massachusetts RTK - Substance List

carbon dioxide (CAS 124-38-9)

isopropyl alcohol (CAS 67-63-0)

naphtha (petroleum), hydrotreated light (CAS 64742-49-0)

n-heptane (CAS 142-82-5)

solvent naphtha (petroleum), light aliph. (CAS 64742-89-8)

US. Pennsylvania Worker and Community Right-to-Know Law

carbon dioxide (CAS 124-38-9)

isopropyl alcohol (CAS 67-63-0)

naphtha (petroleum), hydrotreated light (CAS 64742-49-0)

n-heptane (CAS 142-82-5)

solvent naphtha (petroleum), light aliph. (CAS 64742-89-8)

Material name: Brakleen® Brake Parts Cleaner - 14 oz

No. 05088 (Item# 1003704) Version #: 01 Issue date: 12-16-2021

US. Rhode Island RTK

carbon dioxide (CAS 124-38-9) isopropyl alcohol (CAS 67-63-0) naphtha (petroleum), hydrotreated light (CAS 64742-49-0) n-heptane (CAS 142-82-5) solvent naphtha (petroleum), light aliph. (CAS 64742-89-8)

California Proposition 65



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

California Proposition 65 - CRT: Listed date/Carcinogenic substance

benzene (CAS 71-43-2)

cumene (CAS 98-82-8)

ethylbenzene (CAS 100-41-4)

methyl isobutyl ketone (CAS 108-10-1)

naphthalene (CAS 91-20-3)

Listed: February 27, 1987

Listed: April 6, 2010

Listed: June 11, 2004

Listed: November 4, 2011

Listed: April 19, 2002

California Proposition 65 - CRT: Listed date/Developmental toxin

benzene (CAS 71-43-2)

methanol (CAS 67-56-1)

methyl isobutyl ketone (CAS 108-10-1)

toluene (CAS 108-88-3)

Listed: December 26, 1997

Listed: March 16, 2012

Listed: March 28, 2014

Listed: January 1, 1991

California Proposition 65 - CRT: Listed date/Male reproductive toxin

benzene (CAS 71-43-2) Listed: December 26, 1997 n-hexane (CAS 110-54-3) Listed: December 15, 2017

Volatile organic compounds (VOC) regulations

EPA

VOC content (40 CFR

51.100(s))

Consumer products

Not regulated

95.8 %

(40 CFR 59, Subpt. C)

State

Consumer products

This product is regulated as a Brake Cleaner. This product is not compliant to be sold for use in California, Colorado, Connecticut, Delaware, the District of Columbia, Illinois, Indiana, Maine, Maryland, Massachusetts, Michigan, New Hampshire, New Jersey, New York, Ohio, Pennsylvania, Rhode Island and parts of Utah and Virginia. This product is compliant in all other states.

VOC content (CA) 95.8 % **VOC content (OTC)** 95.8 %

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Industrial Chemicals (AICIS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)
A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing

country(s).

16. Other information, including date of preparation or last revision

Issue date 12-16-2021
Prepared by Danica Fulmer

Version # 01

Further information CRC # 937A/1002953

DisclaimerThe information contained in this document applies to this specific material as supplied. It may not

be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC's knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety

professional, or CRC Industries, Inc..

Revision information This document has undergone significant changes and should be reviewed in its entirety.

Material name: Brakleen® Brake Parts Cleaner - 14 oz

No. 05088 (Item# 1003704) Version #: 01 Issue date: 12-16-2021 11 / 11