

# SAFETY DATA SHEET

## Liqui-Lok Thread Locking Compound

Page: 1 of 9

Revision: 07/22/2020

Supersedes Revision: 08/22/2019

This SDS complies with the Canadian Hazardous Products Regulations of 2015.

### 1. Product and Company Identification

**Product Code:** 250  
**Product Name:** Liqui-Lok Thread Locking Compound  
**Company Name:** Balmar, LLC  
616 W. Pont Des Mouton Rd.  
Lafayette, LA 70507-4002  
**Phone Number:** (337)232-2496  
**Email address:** Info@oilcenter.com  
**Emergency Contact:** CHEMTREC 01 (703)527-3887

### 2. Hazards Identification

**Skin Corrosion/Irritation, Category 2**  
**Serious Eye Damage/Eye Irritation, Category 2A**  
**Skin Sensitization, Category 1**



**GHS Signal Word:** **Warning**

**GHS Hazard Phrases:**  
H315 - Causes skin irritation.  
H317 - May cause an allergic skin reaction.  
H319 - Causes serious eye irritation.

**GHS Precautionary Phrases:**  
P261 - Avoid breathing dust/fume/gas/mist/vapors/spray.  
P264 - Wash hands thoroughly after handling.  
P272 - Contaminated work clothing should not be allowed out of the workplace.  
P280 - Wear protective gloves/protective clothing/eye protection/face protection.

**GHS Response Phrases:**  
P302+352 - IF ON SKIN: Wash with plenty of soap and water.  
P305+351+338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P321 - Specific treatment see First Aid on this label.  
P332+313 - If skin irritation occurs, get medical advice/attention.  
P333+313 - If skin irritation or rash occurs, seek medical advice/attention.  
P337+313 - If eye irritation persists, get medical advice/attention.  
P362+364 - Take off contaminated clothing and wash it before reuse.

**GHS Storage and Disposal Phrases:**  
P501 - Dispose of contents/container to in accordance with all applicable regulations.

**Potential Health Effects (Acute and Chronic):**  
Inhalation is unlikely but in the event that misting occurs, chronic inhalation can cause pneumoconiosis.  
Effects may be delayed.

**Inhalation:**  
May be harmful if inhaled. Causes respiratory tract irritation. Skin: May be harmful if absorbed through skin. May cause skin irritation. Dust is irritating to the respiratory tract. Low hazard for normal industrial handling. Effects may be delayed. Inhalation of fumes may cause metal fume fever, which is characterized by flu-like symptoms with metallic taste, fever, chills, cough, weakness, chest pain, muscle pain and increased white blood cell count. The toxicological properties of this substance have not been fully investigated. Can produce delayed pulmonary edema. However, inhalation fumes or very fine dust may causes "zinc fume fever", which is characterized by flu-like symptoms with metallic taste, coughing, weakness, fatigue, muscular pain, and nausea, followed by fever and chills. Onset of symptoms occurs about 4-12 hours after.

**Skin Contact:**  
May be harmful if absorbed through the skin. Causes skin irritation. Prolonged and/or



# SAFETY DATA SHEET

## Liqui-Lok Thread Locking Compound

Page: 2 of 9

Revision: 07/22/2020  
Supersedes Revision: 08/22/2019

repeated contact may cause irritation and/or dermatitis.

**Eye Contact:** Causes eye irritation. Dust may cause mechanical irritation.

**Ingestion:** May be harmful if swallowed. No hazard expected in normal industrial use. Low hazard for usual industrial handling. Additional Information.

RTECS: QJ6950000 May cause gastrointestinal irritation with nausea, vomiting and diarrhea. Moderately toxic to humans by ingestion. The toxicological properties of this substance have not been fully investigated.

### 3. Composition/Information on Ingredients

CAS #	Components (Chemical Name)	Concentration	
NA	polymer	15 - 40 % **	
NA	metal powder	20.0 - 30.0 %	
NA	nonhazardous additive	20.0 - 30.0 %	
68609-97-2	Oxirane, Mono.((C12-14-alkyloxy)methyl.). derivs.	5.00 - 12.0 %	
NA	coloring agent	1 - 5 % **	
14808-60-7	Quartz	<0.400 %	
NA	Coloring agent	0.1 - 1.0 % **	

\*\* Actual concentration is withheld as a trade secret.

### 4. First Aid Measures

#### Emergency and First Aid

##### Procedures:

##### In Case of Inhalation:

If breathed in, move person into fresh air. Remove from exposure and move to fresh air immediately. If breathing is difficult, give oxygen. Get medical aid if cough or other symptoms appear. Do NOT use mouth-to-mouth resuscitation. If breathing has ceased apply artificial respiration using oxygen and a suitable mechanical device such as a bag and a mask.

##### In Case of Skin Contact:

Wash off with soap and plenty of water. Get medical aid if irritation develops or persists. Wash clothing before reuse.

##### In Case of Eye Contact:

Flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. If irritation develops, get medical aid. Get medical aid.

##### In Case of Ingestion:

Never give anything by mouth to an unconscious person. Do NOT induce vomiting. Wash mouth out with water. If victim is conscious and alert, give 2-4 cupfuls of milk or water. Consult a physician. Get medical aid if irritation or symptoms occur.

##### Signs and Symptoms Of Exposure:

Inhalation is unlikely under normal condition but in the event vapors are produced inhalation of vapors may cause: chills, dry throat, sweet taste, Fever, Cough, Nausea, Vomiting, Weakness. To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated. Prolonged inhalation of crystalline silica may result in silicosis, a disabling pulmonary fibrosis characterized by fibrotic changes and miliary nodules in the lungs, a dry cough, shortness of breath, emphysema, decreased chest expansion, and increased susceptibility to tuberculosis. In advanced stages, loss of appetite, pleuritic pain, and total incapacity to work. Advanced silicosis may result in death due to cardiac failure or destruction of lung tissue. Crystalline silica is classified as group 1 "known to be carcinogenic to humans" by IARC and "sufficient evidence" of carcinogenicity by the NTP.

The chronic health risks are associated with respirable particles of 3-4 um over protracted periods of time.

##### Note to Physician:

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of



**SAFETY DATA SHEET**  
**Liqui-Lok Thread Locking Compound**

Page: 3 of 9

Revision: 07/22/2020  
Supersedes Revision: 08/22/2019

dangerous area. Treat symptomatically and supportively.

### 5. Fire Fighting Measures

**Flash Pt:** None  
**Explosive Limits:** > 204 C (> 400 F) Method Used: Small Scale Open Cup  
LEL: No data. UEL: No data.  
**Autoignition Pt:** No data.  
**Suitable Extinguishing Media:** Use water spray, dry chemical, carbon dioxide, or alcohol-resistant foam. Substance is nonflammable; use agent most appropriate to extinguish surrounding fire. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
**Fire Fighting Instructions:** Wear self contained breathing apparatus for fire fighting if necessary. As in any fire, wear a self-contained breathing apparatus in pressure-demand, MSHA/NIOSH (approved or equivalent), and full protective gear. During a fire, irritating and highly toxic gases may be generated by thermal decomposition or combustion. Material will not burn.  
**Flammable Properties and Hazards:** No data available.  
**Hazardous Combustion Products:** toxic fumes of zinc oxide. irritating and toxic fumes and gases.

### 6. Accidental Release Measures

**Steps To Be Taken In Case Material Is Released Or Spilled:**  
Personal precautions.  
Use personal protective equipment. Avoid breathing vapors, mist or gas. Ensure adequate ventilation.  
Environmental precautions.  
Prevent further leakage or spillage if safe to do so. Do not let product enter drains.  
Discharge of material must be accordance with local and federal regulations.  
Soak up with inert absorbent material and dispose of as hazardous waste. Keep in suitable, closed containers for disposal. Avoid dust formation.  
Methods for cleaning up.  
Sweep up and shovel. Use proper personal protective equipment as indicated in Section 8.  
Spills/Leaks: Clean up spills immediately, observing precautions in the Protective Equipment section. Sweep up or absorb material, then place into a suitable clean, dry, closed container for disposal. Evacuate personnel to safe areas. Pick up and arrange disposal without creating dust.

### 7. Handling and Storage

**Precautions To Be Taken in Handling:** Avoid contact with skin and eyes. Avoid ingestion and inhalation. Avoid inhalation of vapor or mist. Normal measures for preventive fire protection. Use only in a well-ventilated area. Keep container tightly closed. Wash clothing before reuse.  
**Precautions To Be Taken in Storing:** Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in a cool, dry place. Store in a tightly closed container. Keep in a dry place.

### 8. Exposure Controls/Personal Protection

CAS #	Partial Chemical Name	OSHA TWA	ACGIH TWA	Other Limits
NA	polymer	No data.	No data.	No data.
NA	metal powder	No data.	No data.	No data.
NA	nonhazardous additive	PEL: 706 ppm/20 mppcf	TLV: 2 mg/m3	No data.



# SAFETY DATA SHEET

## Liqui-Lok Thread Locking Compound

Page: 4 of 9

Revision: 07/22/2020

Supersedes Revision: 08/22/2019

			(non-asbestos)	
68609-97-2	Oxirane, Mono. (C12-14-alkyloxy)methyl. derivs.	No data.	No data.	No data.
NA	coloring agent	PEL: 5 (fume); 15 (dust) mg/m3	TLV: 2 mg/m3 (R) STEL: 10 mg/m3 (R)	No data.
14808-60-7	Quartz	PEL: 8825 ppm/(%SiO2+5)	TLV: 0.05 mg/m3 (R)	No data.
NA	Coloring agent	PEL: 15 (dust) mg/m3	TLV: 10 mg/m3	No data.

### Respiratory Equipment (Specify Type):

is not required under normal operating conditions. Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi- purpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

### Eye Protection:

Wear appropriate protective eyeglasses or chemical safety goggles as described by OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard EN166.

### Protective Gloves:

For prolonged or repeated contact use protective gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

### Other Protective Clothing:

Wear appropriate protective clothing to minimize contact with skin.

### Engineering Controls (Ventilation etc.):

Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.

### Work/Hygienic/Maintenance Practices:

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday. General industrial hygiene practice.

## 9. Physical and Chemical Properties

### Physical States:

☐ Gas    ☒ Liquid    ☐ Solid

### Appearance and Odor:

Paste.  
weak odor.

Appearance: Silver.

Odor:

### pH:

No data.

### Melting Point:

No data.

### Boiling Point:

No data.

### Flash Pt:

> 204 C (> 400 F)    Method Used: Small Scale Open Cup

### Evaporation Rate:

No data.

### Flammability (solid, gas):

No data available.

### Explosive Limits:

LEL: No data.

UEL: No data.

### Vapor Pressure (vs. Air or mm Hg):

No data.

### Vapor Density (vs. Air = 1):

No data.



# SAFETY DATA SHEET

## Liqui-Lok Thread Locking Compound

Page: 5 of 9

Revision: 07/22/2020  
Supersedes Revision: 08/22/2019

**Specific Gravity (Water = 1):** 1.707 - 1.767 at 25.0 C ( 77.0 F)  
**Density:** 14.25 - 14.75 LB/GA at 25.0 C ( 77.0 F)  
**Solubility in Water:** < 1  
**Octanol/Water Partition Coefficient:** No data.  
**Percent Volatile:** N.A.  
**Autoignition Pt:** No data.  
**Decomposition Temperature:** No data.  
**Viscosity:** No data.

### 10. Stability and Reactivity

**Stability:** Unstable [ ] Stable [ X ]  
**Conditions To Avoid - Instability:** Avoid moisture. Incompatible materials, dust generation.  
**Incompatibility - Materials To Avoid:** Strong oxidizing agents, acids, Amines, Bases, Strong bases, chlorides, fluorine, nitrates, carbon disulfide, Acids. magnesium, chlorinated rubber, Hydrogen fluoride.  
**Hazardous Decomposition or Byproducts:** formed under fire conditions. Nature of decomposition products unknown. Zinc/zinc oxides, irritating and toxic fumes and gases, silicon dioxide, Carbon oxides, toxic fumes of zinc oxide.  
**Possibility of Hazardous Reactions:** Will occur [ ] Will not occur [ X ]  
**Conditions To Avoid - Hazardous Reactions:** No data available.

### 11. Toxicological Information

**Toxicological Information:** Epidemiology: No information available.  
Teratogenicity: No information available.  
Neurotoxicity: Other Studies: No information found.  
Acute toxicity: No data available.  
Respiratory or skin sensitization: Germ cell mutagenicity. Reproductive toxicity - no data available.  
Specific target organ toxicity -single exposure (Globally Harmonized System) Specific target organ toxicity -repeated exposure (Globally Harmonized System)  
Inhalation: May cause damage to organs through prolonged or repeated exposure.  
**Irritation or Corrosion:** No data available.  
**Carcinogenicity/Other Information:** Carcinogenicity.  
IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.  
ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.  
OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA. CAS# 14807-96-6: Not listed by ACGIH, IARC, NTP, or CA Prop 65. CAS# 1314-13-2: Not listed by ACGIH, IARC, NTP, or CA Prop 65. IARC Group 2A: Suspected human carcinogenic substance.  
NTP: Known to be human carcinogen Aluminum arsenide  
Additional studies are needed to determine whether the cell transforming activity of quartz is related to its carcinogenic potential.

**Carcinogenicity:** NTP? No IARC Monographs? No OSHA Regulated? No

CAS #	Components (Chemical Name)	NTP	IARC	ACGIH	OSHA
NA	polymer	n.a.	n.a.	n.a.	n.a.



# SAFETY DATA SHEET

## Liqui-Lok Thread Locking Compound

Page: 6 of 9

Revision: 07/22/2020

Supersedes Revision: 08/22/2019

NA	metal powder	n.a.	n.a.	n.a.	n.a.
NA	nonhazardous additive	n.a.	3	n.a.	n.a.
68609-97-2	Oxirane, Mono.((C12-14-alkyloxy)methyl.). derivs.	n.a.	n.a.	n.a.	n.a.
NA	coloring agent	n.a.	n.a.	n.a.	n.a.
14808-60-7	Quartz	Known	1	A2	n.a.
NA	Coloring agent	n.a.	2B	A4	n.a.

### 12. Ecological Information

#### General Ecological Information:

Toxicity: no data available.  
PBT and vPvB assessment: no data available.  
Other adverse effects.  
An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.  
Toxic to aquatic life with long lasting effects. No data available.  
Elimination information (persistence and degradability)  
Bioaccumulation *Gasterosteus aculeatus* - 25 h.  
Biodegradability aerobic.  
Result: 94,8 % - Readily biodegradable.  
Bioaccumulation: *Lepomis macrochirus* (Bluegill) - 21 d.  
Environmental: Inorganic borates are a water-soluble white powder that may, at high concentrations, cause damage to trees or vegetation by root absorption. No information available.  
Physical: Testing of aquatic toxicity is not meaningful as solubility is poor.  
Other: After exposing rainbow trout to zinc for a period of 30 days in river water, it was concluded that zinc accumulates in the gills, liver, kidney and opercular bone, but not the muscle.

#### Persistence and Degradability:

Biodegradability: Result: 2 % -According to the results of tests of biodegradability this product is not readily biodegradable.

#### Bioaccumulative Potential:

No data available.

#### Mobility in Soil:

No data available.

### 13. Disposal Considerations

#### Waste Disposal Method:

Product.  
Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material.  
Contaminated packaging.  
Dispose of as unused product. Observe all federal, state, and local environmental regulations.  
Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. US EPA guidelines for the classification determination are listed in 40 CFR Parts 261. Additionally, waste generators must consult state and local hazardous waste regulations to ensure complete and accurate classification.  
RCRA P-Series: None listed.  
RCRA U-Series: None listed. Dissolve or mix the material with a combustible solvent and burn in a chemical incinerator equipped with an afterburner and scrubber.

### 14. Transport Information



# SAFETY DATA SHEET

## Liqui-Lok Thread Locking Compound

Page: 7 of 9

Revision: 07/22/2020  
Supersedes Revision: 08/22/2019

### LAND TRANSPORT (US DOT):

DOT Proper Shipping Name: Not regulated as a hazardous material \_per special provision A197.

DOT Hazard Class:

UN/NA Number:

### LAND TRANSPORT (Canadian TDG):

TDG Shipping Name: No information available.

UN Number:

Hazard Class:

TDG Classification:

### LAND TRANSPORT (European ADR/RID):

ADR/RID Shipping Name: No information available.

### MARINE TRANSPORT (IMDG/IMO):

IMDG/IMO Shipping Name: Not regulated as a hazardous material \_per special provision A197.

### AIR TRANSPORT (ICAO/IATA):

ICAO/IATA Shipping Name: Not regulated as a hazardous material \_per special provision A197.

## 15. Regulatory Information

### EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists

CAS #	Components (Chemical Name)	S. 302 (EHS)	S. 304 RQ	S. 313 (TRI)
NA	polymer	No	No	No
NA	metal powder	No	Yes 1000 LB	Yes-Cat. N982
NA	nonhazardous additive	No	No	No
68609-97-2	Oxirane, Mono.((C12-14-alkyloxy)methyl.). derivs.	No	No	No
NA	coloring agent	No	No	Yes-Cat. N982
14808-60-7	Quartz	No	No	No
NA	Coloring agent	No	No	No

### This material meets the EPA 'Hazard Categories' defined for SARA Title III Sections 311/312 as indicated:

<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Explosive	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Acute toxicity (any route of exposure)
<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Flammable (gases, aerosols, liquid, or solid)	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No Skin Corrosion or Irritation
<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Oxidizer (liquid, solid or gas)	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No Serious eye damage or eye irritation
<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Self-reactive	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No Respiratory or Skin Sensitization
<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Pyrophoric (liquid or solid)	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Germ cell mutagenicity
<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Pyrophoric gas	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Carcinogenicity
<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Self-heating	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Reproductive toxicity
<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Organic peroxide	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Specific target organ toxicity (single or repeated exposure)
<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Corrosive to metal	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Aspiration Hazard
<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Gas under pressure (compressed gas)	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Simple Asphyxiant
<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No In contact with water emits flammable gas	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No (Health) Hazard Not Otherwise Classified (HNOC)
<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Combustible Dust	
<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No (Physical) Hazard Not Otherwise Classified (HNOC)	

CAS #	Components (Chemical Name)	Canadian NPRI	Canadian Toxic	Canadian DSL
NA	polymer	No	No	Yes
NA	metal powder	Yes - Cat.		Yes
NA	nonhazardous additive	No	No	Yes
68609-97-2	Oxirane, Mono.((C12-14-alkyloxy)methyl.). derivs.	No	No	Yes
NA	coloring agent	Yes - Cat.		Yes
14808-60-7	Quartz	No	No	Yes
NA	Coloring agent			Yes



# SAFETY DATA SHEET

## Liqui-Lok Thread Locking Compound

Page: 8 of 9

Revision: 07/22/2020

Supersedes Revision: 08/22/2019

CAS #	Components (Chemical Name)	Other US EPA or State Lists
NA	polymer	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No; MA Oil/HazMat: No; NJ EHS: No; NY Part 597: No; PA HSL: No
NA	metal powder	CAA HAP,ODC: No; CWA NPDES: Yes; TSCA: Yes - Inventory, 6A, 12(b); CA PROP.65: No; MA Oil/HazMat: Yes; NJ EHS: Yes; NY Part 597: Yes: HS; PA HSL: Yes - E
NA	nonhazardous additive	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No; MA Oil/HazMat: No; NJ EHS: Yes; NY Part 597: No; PA HSL: Yes - 1
68609-97-2	Oxirane, Mono.((C12-14-alkyloxy)methyl.). derivs.	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory, 8A; CA PROP.65: No; MA Oil/HazMat: No; NJ EHS: No; NY Part 597: No; PA HSL: No
NA	coloring agent	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No; MA Oil/HazMat: Yes - Cat.; NJ EHS: Yes - Cat.; NY Part 597: No; PA HSL: Yes - E
14808-60-7	Quartz	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No; MA Oil/HazMat: No; NJ EHS: No; NY Part 597: No; PA HSL: Yes - 1
NA	Coloring agent	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: Yes: Canc.; MA Oil/HazMat: No; NJ EHS: No; NY Part 597: No; PA HSL: Yes - 1
CAS #	Components (Chemical Name)	International Regulatory Lists
NA	polymer	New Zealand IOC: Yes; REACH: Yes - (R): Full, (P)
NA	metal powder	New Zealand IOC: Yes; REACH: Yes - (R): Full, (P)
NA	nonhazardous additive	New Zealand IOC: Yes; REACH: Yes - (P)
68609-97-2	Oxirane, Mono.((C12-14-alkyloxy)methyl.). derivs.	New Zealand IOC: Yes; REACH: Yes - (R): Full, (P)
NA	coloring agent	New Zealand IOC: Yes; REACH: Yes - (R): Full, (P)
14808-60-7	Quartz	New Zealand IOC: Yes; REACH: Yes - (P)
NA	Coloring agent	New Zealand IOC: Yes; REACH: Yes - (R): Full, (P)

### Canadian WHMIS Classification:



CLASS D, DIVISION 2, SUBDIVISION B: Toxic Materials (Mutagenicity, skin sensitization, irritation, etc.)



# SAFETY DATA SHEET

## Liqui-Lok Thread Locking Compound

Page: 9 of 9

Revision: 07/22/2020  
Supersedes Revision: 08/22/2019


### 16. Other Information

Revision Date: 07/22/2020

Hazard Rating System:

HEALTH		1
FLAMMABILITY		1
PHYSICAL		0
PPE		B

HMIS:



Additional Information About No data available.

This Product:

Company Policy or

Disclaimer:

The information contained here is based upon data available to us and reflects our best professional judgment. Since it is impossible to anticipate the conditions under which our products may be used, we cannot guarantee that the recommendations will be adequate for all individuals and situations. Each user of this product should determine the suitability of the product with zero or minimum hazards. Our products are improved daily as up-to-date information and research data is recieved from our suppliers in our quest to use products with less or no hazards. Please feel free to contact us for current information.