

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 06.21.2019

Page 1 of 11

Epoxy Putty Stick - Steel - Part A

SECTION 1: Identification

Product identifier

Product name: Epoxy Putty Stick - Steel - Part A

Product code: 8267, 8267S, 8267H



Recommended use of the product and restriction on use

Relevant identified uses: Not determined or not applicable.

Uses advised against: Not determined or not applicable.

Reasons why uses advised against: Not determined or not applicable.

Manufacturer or supplier details

Manufacturer:

United States

J-B Weld Company, LLC

400 CMH Road

Sulphur Springs, TX 75482

903-885-7696

info@jbweld.com

Emergency telephone number:

United States

InfoTrac

Transportation Emergencies (24 hour): 800-535-5053

Poison Control Centers (24 hour): medical emergencies 800-222-1222

SECTION 2: Hazard(s) identification

GHS classification:

Skin sensitization, category 1

Eye irritation, category 2A

Skin irritation, category 2

Label elements

Hazard pictograms:



Signal word: Warning

Hazard statements:

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H315 Causes skin irritation.

Precautionary statements:

P261 Avoid breathing dust/fume/gas/mist/vapors/spray.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P264 Wash skin and eyes thoroughly after handling.

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 06.21.2019

Page 2 of 11

Epoxy Putty Stick - Steel - Part A

P321 Specific treatment (see supplemental first aid instructions on this label).

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists get medical advice/attention

P362 Take off contaminated clothing and wash before reuse

P332+P313 If skin irritation occurs: Get medical advice/attention

P501 Dispose of contents/container in accordance with local regulations.

Hazards not otherwise classified: None

SECTION 3: Composition/information on ingredients

Identification	Name	Weight %
CAS number: 14807-96-6	Talc Powder	<40
CAS number: 13463-67-7	Titanium Dioxide	<1
CAS number: 65997-17-3	Powder	<25
CAS number: 3101-60-8	Diluent	<2
CAS number: 25068-38-6	Epoxy resin	<25

Additional Information:

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of the OSHA Hazard Communication Standard (29 CFR §1910.1200).

Fiberglass powder (CAS # 65997-17-3) is classified as a carcinogen in its inhalable form. Since the fiberglass powder in this product is not inhalable, the product itself is not classified as a carcinogen in the form presented.

SECTION 4: First aid measures

Description of first aid measures

General notes:

Not determined or not applicable.

After inhalation:

Loosen clothing as necessary and position individual in a comfortable position

Maintain an unobstructed airway

Get medical advice/attention if you feel unwell

After skin contact:

Rinse affected area with soap and water

If symptoms develop or persist, seek medical attention

Take off all contaminated clothing

Gently blot or brush away excess product

Wash with plenty of lukewarm, gently flowing water

Get medical advice if skin irritation occurs or you feel unwell

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 06.21.2019

Page 3 of 11

Epoxy Putty Stick - Steel - Part A

After eye contact:

Rinse/flush exposed eye(s) gently using water for 15-20 minutes
If symptoms develop or persist, seek medical attention
Rinse eyes cautiously with lukewarm, gently flowing water for several minutes, while holding the eyelids open
Remove contact lenses, if present and easy to do so
Continue rinsing for 15-20 minutes
Get medical advice if eye irritation persists

After swallowing:

Rinse mouth thoroughly
Seek medical attention if irritation, discomfort, or vomiting persists

Most important symptoms and effects, both acute and delayed

Acute symptoms and effects:

Not determined or not applicable.

Delayed symptoms and effects:

Not determined or not applicable.

Immediate medical attention and special treatment

Specific treatment:

Not determined or not applicable.

Notes for the doctor:

Not determined or not applicable.

SECTION 5: Firefighting measures

Extinguishing media

Suitable extinguishing media:

Use appropriate fire suppression agents for adjacent combustible materials or sources of ignition

Unsuitable extinguishing media:

Not determined or not applicable.

Specific hazards during fire-fighting:

Thermal decomposition can lead to release of irritating gases and vapors

Special protective equipment for firefighters:

Use typical firefighting equipment, self-contained breathing apparatus, special tightly sealed suit

Special precautions:

Carbon monoxide and carbon dioxide may form upon combustion
Heating causes a rise in pressure, risk of bursting and combustion

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures:

Ensure adequate ventilation
Ensure air handling systems are operational
Wear protective eye wear, gloves and clothing

Environmental precautions:

Should not be released into the environment
Prevent from reaching drains, sewer or waterway

Methods and material for containment and cleaning up:

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 06.21.2019

Page 4 of 11

Epoxy Putty Stick - Steel - Part A

Wear protective eye wear, gloves and clothing
Sweep or scoop up solid material while minimizing dust generation
Dispose of contents / container in accordance with local regulations

Reference to other sections:

Not determined or not applicable.

SECTION 7: Handling and storage

Precautions for safe handling:

Use only with adequate ventilation.
Avoid breathing dust.
Do not eat, drink, smoke or use personal products when handling chemical substances.

Conditions for safe storage, including any incompatibilities:

Keep container tightly sealed.
Keep container dry.
Store in a cool, well-ventilated area.

SECTION 8: Exposure controls/personal protection

Only those substances with limit values have been included below.

Occupational Exposure limit values:

Country (Legal Basis)	Substance	Identifier	Permissible concentration
United States (OSHA)	Talc Powder	14807-96-6	OSHA PEL Ceiling 20 mppcf
	Titanium Dioxide	13463-67-7	OSHA PEL TWA 15 mg/m ³ (Total dust)
ACGIH	Talc Powder	14807-96-6	ACGIH TLV TWA 2 mg/m ³ ; (Inhalable particulate matter containing no asbestos and < 1% crystalline silica)
	Titanium Dioxide	13463-67-7	ACGIH TLV TWA 10 mg/m ³
	Powder	65997-17-3	8-Hour Exposure Limit (TLV-TWA): 1 fibers/cm ³
NIOSH	Talc Powder	14807-96-6	NIOSH REL TWA 2.0 mg/m ³
	Titanium Dioxide	13463-67-7	IDLH: 5,000 mg/m ³
	Powder	65997-17-3	NIOSH Recommended exposure limit (REL) [for up to a 10-hour workday during a 40-hour workweek] is: 3 fibers/cm ³

Biological limit values:

No biological exposure limits noted for the ingredient(s).

Information on monitoring procedures:

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls.
Biological monitoring may also be appropriate for some substances.

Appropriate engineering controls:

Emergency eye wash fountains and safety showers should be available in the immediate vicinity of use or handling.
Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapor and

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 06.21.2019

Page 5 of 11

Epoxy Putty Stick - Steel - Part A

mists below the applicable workplace exposure limits (Occupational Exposure Limits-OELs) indicated above.

Personal protection equipment

Eye and face protection:

Safety goggles or glasses, or appropriate eye protection.

Skin and body protection:

Select glove material impermeable and resistant to the substance.

Wear appropriate clothing to prevent any possibility of skin contact.

Respiratory protection:

If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn.

General hygienic measures:

Avoid contact with skin, eyes and clothing.

Wash hands before breaks and at the end of work.

Wash contaminated clothing before reuse.

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties

Appearance	Very thick black paste (solid)
Odor	Not determined or not available.
Odor threshold	Not determined or not available.
pH	Not determined or not available.
Melting point/freezing point	Not determined or not available.
Initial boiling point/range	Not determined or not available.
Flash point (closed cup)	135°C (275°F)
Evaporation rate	Not determined or not available.
Flammability (solid, gas)	Not determined or not available.
Upper flammability/explosive limit	Not determined or not available.
Lower flammability/explosive limit	Not determined or not available.
Vapor pressure	Not determined or not available.
Vapor density	Not determined or not available.
Density	2.15
Relative density	Not determined or not available.
Solubilities	Not determined or not available.
Partition coefficient (n-octanol/water)	Not determined or not available.
Auto/Self-ignition temperature	Not determined or not available.
Decomposition temperature	Not determined or not available.
Dynamic viscosity	Not determined or not available.
Kinematic viscosity	Not determined or not available.
Explosive properties	Not determined or not available.
Oxidizing properties	Not determined or not available.

Other information

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 06.21.2019

Page 6 of 11

Epoxy Putty Stick - Steel - Part A

SECTION 10: Stability and reactivity

Reactivity:

Does not react under normal conditions of use and storage.

Chemical stability:

Stable under normal conditions of use and storage.

Possibility of hazardous reactions:

None under normal conditions of use and storage.

Conditions to avoid:

None known.

Incompatible materials:

None known.

Hazardous decomposition products:

None known.

SECTION 11: Toxicological information

Acute toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Substance data: No data available.

Skin corrosion/irritation**Assessment:**

Causes skin irritation

Product data:

No data available.

Substance data:

Name	Result
Epoxy resin	Causes skin irritation.
Diluent	Causes skin irritation

Serious eye damage/irritation**Assessment:**

Causes serious eye irritation

Product data:

No data available.

Substance data:

Name	Result
Epoxy resin	Causes serious eye irritation.
Diluent	Causes serious eye damage

Respiratory or skin sensitization**Assessment:**

May cause an allergic skin reaction

Product data:

No data available.

Substance data:

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 06.21.2019

Page 7 of 11

Epoxy Putty Stick - Steel - Part A

Name	Result
Epoxy resin	May cause an allergic skin reaction.
Diluent	Result : May cause sensitisation by skin contact.

Carcinogenicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Substance data:

Name	Species	Result
Powder	Not applicable	May cause cancer via inhalation.
Titanium Dioxide	Not applicable.	Airborne, unbound particles of respirable size are known to cause cancer.

International Agency for Research on Cancer (IARC):

Name	Classification
Talc Powder	Group 3 - Not classifiable as to its carcinogenicity to humans
Powder	Group 2B
Titanium Dioxide	Group 2B

National Toxicology Program (NTP):

Name	Classification
Powder	Reasonably anticipated to be human carcinogens

Germ cell mutagenicity

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data: No data available.

Reproductive toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data: No data available.

Specific target organ toxicity (single exposure)

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data: No data available.

Specific target organ toxicity (repeated exposure)

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data: No data available.

Aspiration toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 06.21.2019

Page 8 of 11

Epoxy Putty Stick - Steel - Part A

Substance data: No data available.

Information on likely routes of exposure:

No data available.

Symptoms related to the physical, chemical and toxicological characteristics:

No data available.

Other information:

No data available.

SECTION 12: Ecological information

Acute (short-term) toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Substance data:

Name	Result
Epoxy resin	EC50 - Scenedesmus capricornutum - 9 mg/L - 48 h

Chronic (long-term) toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Substance data: No data available.

Persistence and degradability

Product data: No data available.

Substance data: No data available.

Bioaccumulative potential

Product data: No data available.

Substance data: No data available.

Mobility in soil

Product data: No data available.

Substance data: No data available.

Other adverse effects: No data available.

SECTION 13: Disposal considerations

Disposal methods:

It is the responsibility of the waste generator to properly characterize all waste materials according to applicable regulatory entities

SECTION 14: Transport information

United States Transportation of dangerous goods (49 CFR DOT)

UN number	Not Regulated
UN proper shipping name	Not Regulated
UN transport hazard class(es)	None
Packing group	None
Environmental hazards	None
Special precautions for user	None

International Maritime Dangerous Goods (IMDG)

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 06.21.2019

Page 9 of 11

Epoxy Putty Stick - Steel - Part A

UN number	UN 3077
UN proper shipping name	Environmentally hazardous substance, Solid, N.O.S. (Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2-(chloromethyl)oxiran, P-tert-butylphenyl 1-(2,3-epoxy)propyl ether)
UN transport hazard class(es)	9 
Packing group	III
Environmental hazards	Marine Pollutant (Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2-(chloromethyl)oxiran, P-tert-butylphenyl 1-(2,3-epoxy)propyl ether)
Special precautions for user	None

International Air Transport Association Dangerous Goods Regulations (IATA-DGR)

UN number	UN 3077
UN proper shipping name	Environmentally hazardous substance, Solid, N.O.S. (Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2-(chloromethyl)oxiran, P-tert-butylphenyl 1-(2,3-epoxy)propyl ether)
UN transport hazard class(es)	9 
Packing group	III
Environmental hazards	Marine Pollutant (Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2-(chloromethyl)oxiran, P-tert-butylphenyl 1-(2,3-epoxy)propyl ether)
Special precautions for user	None

Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Bulk Name	None
Ship type	None
Pollution category	None

SECTION 15: Regulatory information

United States regulations

Inventory listing (TSCA):

25068-38-6	Epoxy resin	Listed
3101-60-8	Diluent	Listed
14807-96-6	Talc Powder	Listed
65997-17-3	Powder	Listed
13463-67-7	Titanium Dioxide	Listed

Significant New Use Rule (TSCA Section 5): None of the ingredients are listed.

Export notification under TSCA Section 12(b): None of the ingredients are listed.

SARA Section 302 extremely hazardous substances: None of the ingredients are listed.

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 06.21.2019

Page 10 of 11

Epoxy Putty Stick - Steel - Part A

SARA Section 313 toxic chemicals: None of the ingredients are listed.

CERCLA: None of the ingredients are listed.

RCRA: None of the ingredients are listed.

Section 112(r) of the Clean Air Act (CAA): None of the ingredients are listed.

Massachusetts Right to Know:

25068-38-6	Epoxy resin	Not Listed
3101-60-8	Diluent	Not Listed
14807-96-6	Talc Powder	Listed
65997-17-3	Powder	Listed
13463-67-7	Titanium Dioxide	Listed

New Jersey Right to Know:

25068-38-6	Epoxy resin	Not Listed
3101-60-8	Diluent	Not Listed
14807-96-6	Talc Powder	Listed
65997-17-3	Powder	Listed
13463-67-7	Titanium Dioxide	Listed

New York Right to Know:

25068-38-6	Epoxy resin	Not Listed
3101-60-8	Diluent	Not Listed
14807-96-6	Talc Powder	Not Listed
65997-17-3	Powder	Not Listed
13463-67-7	Titanium Dioxide	Listed

Pennsylvania Right to Know:

25068-38-6	Epoxy resin	Not Listed
3101-60-8	Diluent	Not Listed
14807-96-6	Talc Powder	Listed
65997-17-3	Powder	Listed
13463-67-7	Titanium Dioxide	Listed

California Proposition 65: None of the ingredients are listed.

SECTION 16: Other information

Abbreviations and Acronyms: None

Disclaimer:

This product has been classified in accordance with OSHA HCS 2012 guidelines. The information provided in this SDS is correct, to the best of our knowledge, based on information available. The information given is

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 06.21.2019

Page 11 of 11

Epoxy Putty Stick - Steel - Part A

designed only as a guidance for safe handling, use, storage, transportation and disposal and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials, unless specified in the text. The responsibility to provide a safe workplace remains with the user.

NFPA: 2-0-0

HMIS: 2-0-0

Initial preparation date: 06.21.2019

End of Safety Data Sheet

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 06.21.2019

Page 1 of 10

Epoxy Putty Stick - Steel - Part B

SECTION 1: Identification

Product identifier

Product name: Epoxy Putty Stick - Steel - Part B

Product code: 8267, 8267S, 8267H B



Recommended use of the product and restriction on use

Relevant identified uses: Not determined or not applicable.

Uses advised against: Not determined or not applicable.

Reasons why uses advised against: Not determined or not applicable.

Manufacturer or supplier details

Manufacturer:

United States

J-B Weld Company, LLC
400 CMH Road
Sulphur Springs, TX 75482
903-885-7696
info@jbweld.com

Emergency telephone number:

United States

InfoTrac

Transportation Emergencies (24 hour): 800-535-5053

Poison Control Centers (24 hour): medical emergencies 800-222-1222

SECTION 2: Hazard(s) identification

GHS classification:

Skin sensitization, category 1

Label elements

Hazard pictograms:



Signal word: Warning

Hazard statements:

H317 May cause an allergic skin reaction.

Precautionary statements:

P261 Avoid breathing dust/fume/gas/mist/vapors/spray.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P321 Specific treatment (see supplemental first aid instructions on this label).

P363 Wash contaminated clothing before reuse

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P333+P313 If skin irritation or a rash occurs: Get medical advice/attention

P501 Dispose of contents and container in accordance with local regulations.

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 06.21.2019

Page 2 of 10

Epoxy Putty Stick - Steel - Part B

Hazards not otherwise classified: None

SECTION 3: Composition/information on ingredients

Identification	Name	Weight %
CAS number: 1333-86-4	Bounded Carbon Black	<1
CAS number: 14807-96-6	Talc Powder	<40
CAS number: 65997-17-3	Powder	<20
CAS number: 90-72-2	Amine curing agent	<5
CAS number: 72244-98-5	Curing Agent	<25

Additional Information:

Fiberglass powder (CAS # 65997-17-3) is classified as a carcinogen in its inhalable form. Since the fiberglass powder in this product is not inhalable, the product itself is not classified as a carcinogen in the form presented.

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of the OSHA Hazard Communication Standard (29 CFR §1910.1200).

Carbon black is classified as a carcinogen only in its respirable form. Since the carbon black in this product is not respirable, the product itself is not classified as a carcinogen in the form presented.

SECTION 4: First aid measures

Description of first aid measures

General notes:

Not determined or not applicable.

After inhalation:

Loosen clothing as necessary and position individual in a comfortable position

Maintain an unobstructed airway

Get medical advice/attention if you feel unwell

After skin contact:

Rinse affected area with soap and water

If symptoms develop or persist, seek medical attention

After eye contact:

Rinse/flush exposed eye(s) gently using water for 15-20 minutes

If symptoms develop or persist, seek medical attention

After swallowing:

Rinse mouth thoroughly

Seek medical attention if irritation, discomfort, or vomiting persists

Most important symptoms and effects, both acute and delayed

Acute symptoms and effects:

Not determined or not applicable.

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 06.21.2019

Page 3 of 10

Epoxy Putty Stick - Steel - Part B

Delayed symptoms and effects:

Not determined or not applicable.

Immediate medical attention and special treatment**Specific treatment:**

Not determined or not applicable.

Notes for the doctor:

Not determined or not applicable.

SECTION 5: Firefighting measures

Extinguishing media**Suitable extinguishing media:**

Use appropriate fire suppression agents for adjacent combustible materials or sources of ignition

Unsuitable extinguishing media:

Not determined or not applicable.

Specific hazards during fire-fighting:

Thermal decomposition can lead to release of irritating gases and vapors

Special protective equipment for firefighters:

Use typical firefighting equipment, self-contained breathing apparatus, special tightly sealed suit

Special precautions:

Carbon monoxide and carbon dioxide may form upon combustion

Heating causes a rise in pressure, risk of bursting and combustion

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures:

Ensure adequate ventilation

Ensure air handling systems are operational

Wear protective eye wear, gloves and clothing

Environmental precautions:

Should not be released into the environment

Prevent from reaching drains, sewer or waterway

Methods and material for containment and cleaning up:

Wear protective eye wear, gloves and clothing

Sweep or scoop up solid material while minimizing dust generation

Dispose of contents / container in accordance with local regulations

Reference to other sections:

Not determined or not applicable.

SECTION 7: Handling and storage

Precautions for safe handling:

Use only with adequate ventilation.

Avoid breathing dust.

Do not eat, drink, smoke or use personal products when handling chemical substances.

Conditions for safe storage, including any incompatibilities:

Keep container tightly sealed.

Keep container dry.

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 06.21.2019

Page 4 of 10

Epoxy Putty Stick - Steel - Part B

Store in a cool, well-ventilated area.

SECTION 8: Exposure controls/personal protection

Only those substances with limit values have been included below.

Occupational Exposure limit values:

Country (Legal Basis)	Substance	Identifier	Permissible concentration
United States (OSHA)	Talc Powder	14807-96-6	OSHA PEL Ceiling 20 mppcf
	Bounded Carbon Black	1333-86-4	OSHA PEL TWA 3.5 mg/m ³
ACGIH	Talc Powder	14807-96-6	ACGIH TLV TWA 2 mg/m ³ ; (Inhalable particulate matter containing no asbestos and < 1% crystalline silica)
	Bounded Carbon Black	1333-86-4	TLV-TWA 3.0 mg/m ³
	Powder	65997-17-3	8-Hour Exposure Limit (TLV-TWA): 1 fibers/cm ³
NIOSH	Talc Powder	14807-96-6	NIOSH REL TWA 2.0 mg/m ³
	Bounded Carbon Black	1333-86-4	NIOSH REL TWA 0.1 mg PAHs/m ³ [Carbon black in presence of polycyclic aromatic hydrocarbons (PAHs)]
	Bounded Carbon Black	1333-86-4	NIOSH REL TWA 3.5 mg/m ³ Ca
	Powder	65997-17-3	NIOSH Recommended exposure limit (REL) [for up to a 10-hour workday during a 40-hour workweek] is: 3 fibers/cm ³

Biological limit values:

No biological exposure limits noted for the ingredient(s).

Information on monitoring procedures:

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls.

Biological monitoring may also be appropriate for some substances.

Appropriate engineering controls:

Emergency eye wash fountains and safety showers should be available in the immediate vicinity of use or handling.

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapor and mists below the applicable workplace exposure limits (Occupational Exposure Limits-OELs) indicated above.

Personal protection equipment

Eye and face protection:

Safety goggles or glasses, or appropriate eye protection.

Skin and body protection:

Select glove material impermeable and resistant to the substance.

Wear appropriate clothing to prevent any possibility of skin contact.

Respiratory protection:

If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn.

General hygienic measures:

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 06.21.2019

Page 5 of 10

Epoxy Putty Stick - Steel - Part B

Avoid contact with skin, eyes and clothing.
Wash hands before breaks and at the end of work.
Wash contaminated clothing before reuse.

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties

Appearance	Very thick grey paste (solid)
Odor	Not determined or not available.
Odor threshold	Not determined or not available.
pH	Not determined or not available.
Melting point/freezing point	Not determined or not available.
Initial boiling point/range	Not determined or not available.
Flash point (closed cup)	148.89°C (300°F)
Evaporation rate	Not determined or not available.
Flammability (solid, gas)	Not determined or not available.
Upper flammability/explosive limit	Not determined or not available.
Lower flammability/explosive limit	Not determined or not available.
Vapor pressure	Not determined or not available.
Vapor density	Not determined or not available.
Density	2.1 g/cm ³
Relative density	Not determined or not available.
Solubilities	Not determined or not available.
Partition coefficient (n-octanol/water)	Not determined or not available.
Auto/Self-ignition temperature	Not determined or not available.
Decomposition temperature	Not determined or not available.
Dynamic viscosity	Not determined or not available.
Kinematic viscosity	Not determined or not available.
Explosive properties	Not determined or not available.
Oxidizing properties	Not determined or not available.

Other information

SECTION 10: Stability and reactivity

Reactivity:

Does not react under normal conditions of use and storage.

Chemical stability:

Stable under normal conditions of use and storage.

Possibility of hazardous reactions:

None under normal conditions of use and storage.

Conditions to avoid:

None known.

Incompatible materials:

None known.

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 06.21.2019

Page 6 of 10

Epoxy Putty Stick - Steel - Part B

Hazardous decomposition products:

None known.

SECTION 11: Toxicological information

Acute toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Substance data:

Name	Route	Result
Amine curing agent	oral	LD50 - Rat - 1,200 mg/kg

Skin corrosion/irritation

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data:

Name	Result
Amine curing agent	Causes skin irritation.

Serious eye damage/irritation

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data:

Name	Result
Amine curing agent	Causes serious eye irritation.

Respiratory or skin sensitization

Assessment:

May cause an allergic skin reaction

Product data:

No data available.

Substance data:

Name	Result
Curing Agent	May cause an allergic skin reaction.

Carcinogenicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Substance data:

Name	Species	Result
Powder	Not applicable	May cause cancer via inhalation.
Bounded Carbon Black	Not applicable.	The carcinogenic classification only applies to airborne, unbound particles of respirable size.

International Agency for Research on Cancer (IARC):

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 06.21.2019

Page 7 of 10

Epoxy Putty Stick - Steel - Part B

Name	Classification
Powder	Group 2B
Talc Powder	Group 3 - Not classifiable as to its carcinogenicity to humans
Bounded Carbon Black	Group 2B - Possibly carcinogenic to humans

National Toxicology Program (NTP):

Name	Classification
Powder	Reasonably anticipated to be human carcinogens

Germ cell mutagenicity

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data: No data available.

Reproductive toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data: No data available.

Specific target organ toxicity (single exposure)

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data: No data available.

Specific target organ toxicity (repeated exposure)

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data: No data available.

Aspiration toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data: No data available.

Information on likely routes of exposure:

No data available.

Symptoms related to the physical, chemical and toxicological characteristics:

No data available.

Other information:

No data available.

SECTION 12: Ecological information

Acute (short-term) toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Substance data: No data available.

Chronic (long-term) toxicity

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 06.21.2019

Page 8 of 10

Epoxy Putty Stick - Steel - Part B

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Substance data:

Name	Result
Curing Agent	NOEC - Daphnia magna (Water flea) - 3.5 mg/L - 21 d

Persistence and degradability

Product data: No data available.

Substance data: No data available.

Bioaccumulative potential

Product data: No data available.

Substance data: No data available.

Mobility in soil

Product data: No data available.

Substance data: No data available.

Other adverse effects: No data available.

SECTION 13: Disposal considerations

Disposal methods:

It is the responsibility of the waste generator to properly characterize all waste materials according to applicable regulatory entities

SECTION 14: Transport information

United States Transportation of dangerous goods (49 CFR DOT)

UN number	Not Regulated
UN proper shipping name	Not Regulated
UN transport hazard class(es)	None
Packing group	None
Environmental hazards	None
Special precautions for user	None

International Maritime Dangerous Goods (IMDG)

UN number	Not Regulated
UN proper shipping name	Not Regulated
UN transport hazard class(es)	None
Packing group	None
Environmental hazards	None
Special precautions for user	None

International Air Transport Association Dangerous Goods Regulations (IATA-DGR)

UN number	Not Regulated
UN proper shipping name	Not Regulated
UN transport hazard class(es)	None
Packing group	None

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 06.21.2019

Page 9 of 10

Epoxy Putty Stick - Steel - Part B

Environmental hazards	None
Special precautions for user	None

Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	
Bulk Name	None
Ship type	None
Pollution category	None

SECTION 15: Regulatory information

United States regulations

Inventory listing (TSCA):

72244-98-5	Curing Agent	Listed
90-72-2	Amine curing agent	Listed
65997-17-3	Powder	Listed
14807-96-6	Talc Powder	Listed
1333-86-4	Bounded Carbon Black	Listed

Significant New Use Rule (TSCA Section 5): None of the ingredients are listed.

Export notification under TSCA Section 12(b): None of the ingredients are listed.

SARA Section 302 extremely hazardous substances: None of the ingredients are listed.

SARA Section 313 toxic chemicals: None of the ingredients are listed.

CERCLA: None of the ingredients are listed.

RCRA: None of the ingredients are listed.

Section 112(r) of the Clean Air Act (CAA): None of the ingredients are listed.

Massachusetts Right to Know:

72244-98-5	Curing Agent	Not Listed
90-72-2	Amine curing agent	Not Listed
65997-17-3	Powder	Listed
14807-96-6	Talc Powder	Listed
1333-86-4	Bounded Carbon Black	Listed

New Jersey Right to Know:

1333-86-4	Bounded Carbon Black	Listed
72244-98-5	Curing Agent	Not Listed
90-72-2	Amine curing agent	Not Listed
65997-17-3	Powder	Listed
14807-96-6	Talc Powder	Listed

New York Right to Know: None of the ingredients are listed.

Pennsylvania Right to Know:

1333-86-4	Bounded Carbon Black	Listed
-----------	----------------------	--------

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 06.21.2019

Page 10 of 10

Epoxy Putty Stick - Steel - Part B

72244-98-5	Curing Agent	Not Listed
90-72-2	Amine curing agent	Not Listed
65997-17-3	Powder	Listed
14807-96-6	Talc Powder	Listed

California Proposition 65: None of the ingredients are listed.

SECTION 16: Other information

Abbreviations and Acronyms: None

Disclaimer:

This product has been classified in accordance with OSHA HCS 2012 guidelines. The information provided in this SDS is correct, to the best of our knowledge, based on information available. The information given is designed only as a guidance for safe handling, use, storage, transportation and disposal and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials, unless specified in the text. The responsibility to provide a safe workplace remains with the user.

NFPA: 2-0-0

HMIS: 2-0-0

Initial preparation date: 06.21.2019

End of Safety Data Sheet